



## SAFETY DATA SHEET

## **DOW CHEMICAL COMPANY LIMITED**

Safety Data Sheet according to Reg. (EU) No 2015/830

Product name: GREAT STUFF PRO™ Gun Foam B1 750ml

Revision Date: 03.11.2016 Version: 10.0

Print Date: 04.11.2016

DOW CHEMICAL COMPANY LIMITED encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

## 1.1 Product identifier

Product name: GREAT STUFF PRO™ Gun Foam B1 750ml

## 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Identified uses:** Cavity sealing foam.

## 1.3 Details of the supplier of the safety data sheet COMPANY IDENTIFICATION

DOW CHEMICAL COMPANY LIMITED DIAMOND HOUSE, LOTUS PARK, KINGSBURY CRESCENT, STAINES England TW18 3AG UNITED KINGDOM

Customer Information Number: +44 (0) 203 139 4000 SDSQuestion@dow.com

## 1.4 EMERGENCY TELEPHONE NUMBER

**24-Hour Emergency Contact:** 0031 115 694 982 **Local Emergency Contact:** 00 31 115 69 4982

## **SECTION 2: HAZARDS IDENTIFICATION**

## 2.1 Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008:

Aerosols - Category 1 - H222, H229 Skin irritation - Category 2 - H315 Eye irritation - Category 2 - H319 Respiratory sensitisation - Category 1 - H334 Skin sensitisation - Category 1 - H317 Carcinogenicity - Category 2 - H351

**Product name: GREAT STUFF PRO™ Gun Foam B1 750ml**Revision Date: 03.11.2016

Version: 10.0

Specific target organ toxicity - single exposure - Category 3 - H335 Specific target organ toxicity - repeated exposure - Category 2 - H373 For the full text of the H-Statements mentioned in this Section, see Section 16.

#### 2.2 Label elements

## Labelling according to Regulation (EC) No 1272/2008:

## **Hazard pictograms**



## Signal word: DANGER

## **Hazard statements**

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H373	May cause damage to organs (Respiratory Tract) through prolonged or repeated
	exposure.

#### **Precautionary statements**

, , , , , , , , , , , , , , , , , , , ,	***************************************
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
	No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe spray.
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a
+ P312	POISON CENTER/doctor if you feel unwell.
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

## **Contains** Diphenylmethane Diisocyanate, isomers and homologues

## 2.3 Other hazards

Persons already sensitised to diisocyanates may develop allergic reactions when using this product. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.

This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

**Product name: GREAT STUFF PRO™ Gun Foam B1 750ml**Revision Date: 03.11.2016

Version: 10.0

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

## 3.2 Mixtures

This product is a mixture.

CASRN / EC-No. / Index-No.	REACH Registration Number	Concentration	Component	Classification: REGULATION (EC) No 1272/2008
CASRN Not available EC-No. Polymer Index-No.	-	25.0 - 45.0 %	Prepolymer of MDI and polyol	Resp. Sens 1 - H334 Skin Sens 1 - H317
CASRN 9016-87-9 EC-No. 618-498-9 Index-No.	_	15.0 - 35.0 %	Diphenylmethane Diisocyanate, isomers and homologues	Acute Tox 4 - H332 Skin Irrit 2 - H315 Eye Irrit 2 - H319 Resp. Sens 1 - H334 Skin Sens 1 - H317 Carc 2 - H351 STOT SE - 3 - H335 STOT RE - 2 - H373
CASRN 13674-84-5 EC-No. 237-158-7 Index-No.	01-2119486772-26	15.0 - < 25.0 %	Tris(1-chloro-2- propyl) phosphate	Acute Tox 4 - H302
CASRN 101-68-8 EC-No. 202-966-0 Index-No. 615-005-00-9	01-2119457014-47	5.0 - 15.0 %	4,4'- methylenediphenyl diisocyanate	Acute Tox 4 - H332 Skin Irrit 2 - H315 Eye Irrit 2 - H319 Resp. Sens 1 - H334 Skin Sens 1 - H317 Carc 2 - H351 STOT SE - 3 - H335 STOT RE - 2 - H373
CASRN 115-10-6 EC-No. 204-065-8 Index-No. 603-019-00-8	_	3.0 - 7.0 %	dimethyl ether	Flam. Gas - 1 - H220 Press. Gas - Liquefied gas - H280



**Product name: GREAT STUFF PRO™ Gun Foam B1 750ml** Revision Date: 03.11.2016

Version: 10.0

CASRN 74-98-6 EC-No. 200-827-9 Index-No. 601-003-00-5	01-2119486944-21	2.0 - 5.0 %	propane	Flam. Gas - 1 - H220 Press. Gas - Compr. Gas - H280
CASRN 75-28-5 EC-No. 200-857-2 Index-No. 601-004-00-0	01-2119485395-27	2.0 - 5.0 %	Isobutane	Flam. Gas - 1 - H220 Press. Gas - Compr. Gas - H280

For the full text of the H-Statements mentioned in this Section, see Section 16.

Note

Note: CAS 101-68-8 is an MDI isomer that is part of CAS 9016-87-9.

#### **SECTION 4: FIRST AID MEASURES**

## 4.1 Description of first aid measures

**General advice:** First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

**Inhalation:** Move person to fresh air. If not breathing, give artificial respiration; if by mouth to mouth use rescuer protection (pocket mask, etc). If breathing is difficult, oxygen should be administered by qualified personnel. Call a physician or transport to a medical facility.

**Skin contact:** Remove material from skin immediately by washing with soap and plenty of water. Remove contaminated clothing and shoes while washing. Seek medical attention if irritation persists. Wash clothing before reuse. An MDI skin decontamination study demonstrated that cleaning very soon after exposure is important, and that a polyglycol-based skin cleanser or corn oil may be more effective than soap and water. Discard items which cannot be decontaminated, including leather articles such as shoes, belts and watchbands. Suitable emergency safety shower facility should be available in work area.

**Eye contact:** Immediately flush eyes with water; remove contact lenses, if present, after the first 5 minutes, then continue flushing eyes for at least 15 minutes. Obtain medical attention without delay, preferably from an ophthalmologist. Suitable emergency eye wash facility should be immediately available.

**Ingestion:** Do not induce vomiting. Call a physician and/or transport to emergency facility immediately.

**4.2 Most important symptoms and effects, both acute and delayed:** Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

T: 020 7703 9786

Unit 9 Deptford Trading Estate, Blackhorse Road, London, SE8 5HY

FLINT: Theatrical Chand

Product name: GREAT STUFF PRO™ Gun Foam B1 750ml Revision Date: 03.11.2016

Version: 10.0

## 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician: Maintain adequate ventilation and oxygenation of the patient. May cause respiratory sensitization or asthma-like symptoms. Bronchodilators, expectorants and antitussives may be of help. Treat bronchospasm with inhaled beta2 agonist and oral or parenteral corticosteroids. Respiratory symptoms, including pulmonary edema, may be delayed. Persons receiving significant exposure should be observed 24-48 hours for signs of respiratory distress. If you are sensitized to diisocyanates, consult your physician regarding working with other respiratory irritants or sensitizers. Attempt seizure control with diazepam 5-10 mg (adults) intravenous over 2-3 minutes. Repeat every 5-10 minutes as needed. Monitor for hypotension, respiratory depression, and need for intubation. Consider second agent if seizures persist after 30 mg. If seizures persist or recur administer phenobarbital 600-1200 mg (adults) intravenous diluted in 60 ml 0.9% saline given at 25-50 mg/minute. Evaluate for hypoxia, dysrhythmia, electrolyte disturbance, hypoglycemia (treat adults with dextrose 100 mg intravenous). Exposure may increase "myocardial irritability". Do not administer sympathomimetic drugs such as epinephrine unless absolutely necessary. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient. Excessive exposure may aggravate preexisting asthma and other respiratory disorders (e.g. emphysema, bronchitis, reactive airways dysfunction syndrome).

## **SECTION 5: FIREFIGHTING MEASURES**

#### 5.1 Extinguishing media

**Suitable extinguishing media:** Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam. Alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams may function, but will be less effective.

**Unsuitable extinguishing media:** Do not use direct water stream. Straight or direct water streams may not be effective to extinguish fire.

#### 5.2 Special hazards arising from the substance or mixture

**Hazardous combustion products:** During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Nitrogen oxides. Isocyanates. Hydrogen chloride. Carbon monoxide. Carbon dioxide. Hydrogen cyanide.

**Unusual Fire and Explosion Hazards:** Contains flammable propellant. Aerosol cans exposed to fire can rupture and become flaming projectiles. Propellant release may result in a fireball. Vapors are heavier than air and may travel a long distance and accumulate in low lying areas. Ignition and/or flash back may occur. Dense smoke is produced when product burns.

#### 5.3 Advice for firefighters

**Fire Fighting Procedures:** Keep people away. Isolate fire and deny unnecessary entry. Stay upwind. Keep out of low areas where gases (fumes) can accumulate. Water may not be effective in extinguishing fire. Do not use direct water stream. May spread fire. Fight fire from protected location or safe distance. Consider the use of unmanned hose holders or monitor nozzles. Eliminate ignition sources. Move container from fire area if this is possible without hazard. Use water spray to cool fire-exposed containers and fire-affected zone until fire is out.

**Special protective equipment for firefighters:** Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). Avoid contact with this material during fire fighting operations. If contact is likely, change to full chemical resistant fire fighting clothing with self-contained breathing apparatus. If this is

Product name: GREAT STUFF PRO™ Gun Foam B1 750ml

Version: 10.0

**Revision Date: 03.11.2016** 

not available, wear full chemical resistant clothing with self-contained breathing apparatus and fight fire from a remote location. For protective equipment in post-fire or non-fire clean-up situations, refer to the relevant sections.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

- **6.1 Personal precautions, protective equipment and emergency procedures:** Only trained and properly protected personnel must be involved in clean-up operations. Keep unnecessary and unprotected personnel from entering the area. If available, use foam to suppress vapors. Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection. See Section 10 for more specific information.
- **6.2 Environmental precautions:** Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.
- **6.3 Methods and materials for containment and cleaning up:** Spills should be contained by, and covered with large quantities of sand, earth or any other readily available absorbent material which is then brushed in vigorously to assist absorption. The mixture can then be collected into drums and removed for disposal. Wash area from residues with soap and water and rinse down.
- **6.4 Reference to other sections:** References to other sections, if applicable, have been provided in the previous sub-sections.

## SECTION 7: HANDLING AND STORAGE

**7.1 Precautions for safe handling:** Keep away from heat, sparks and flame. Use only with adequate ventilation.

Spills of these organic materials on hot fibrous insulations may lead to lowering of the autoignition temperatures possibly resulting in spontaneous combustion.

**7.2 Conditions for safe storage, including any incompatibilities:** Keep in a cool, well-ventilated place. Keep away from sources of ignition - No smoking. See Section 10 for more specific information.

Storage stability

Storage temperature: Storage Period: 15 - 25 °C 18 Month

7.3 Specific end use(s): See the technical data sheet on this product for further information.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters

Exposure limits are listed below, if they exist.

 Component
 Regulation
 Type of listing
 Value/Notation

 Diphenylmethane
 GB EH40
 TWA
 SEN

Diisocyanate, isomers and

homologues

Product name: GREAT STUFF PRO™ Gun Foam B1 750ml Revision Date: 03.11.2016
Version: 10.0

	GB EH40	STEL	SEN
	GB EH40	TWA	0.02 mg/m3 , NCO
	GB EH40	STEL	0.07 mg/m3 , NCO
4,4'-methylenediphenyl	ACGIH	TWA	0.005 ppm
diisocyanate			
•	Dow IHG	TWA	0.005 ppm
	Dow IHG	STEL	0.02 ppm
	GB EH40	TWA	SEN
	GB EH40	STEL	SEN
	GB EH40	TWA	0.02 mg/m3 , NCO
	GB EH40	STEL	0.07 mg/m3 , NCO
dimethyl ether	US WEEL	TWA	1,000 ppm
,	2000/39/EC	TWA	1,920 mg/m3 1,000
			ppm
	GB EH40	TWA	766 mg/m3 400 ppm
	GB EH40	STEL	958 mg/m3 500 ppm
propane	ACGIH		Asphyxiant
İsobutane	ACGIH	STEL	1,000 ppm

This material contains a simple asphyxiant which may displace oxygen. Insure adequate ventilation to prevent an oxygen deficient atmosphere.

The minimum requirement of 19.5% oxygen at sea level (148 torr O2, dry air) provides an adequate amount of oxygen for most work assignments.

## 8.2 Exposure controls

**Engineering controls:** Use only with adequate ventilation. Local exhaust ventilation may be necessary for some operations. Provide general and/or local exhaust ventilation to control airborne levels below the exposure guidelines. Exhaust systems should be designed to move the air away from the source of vapor/aerosol generation and people working at this point. The odor and irritancy of this material are inadequate to warn of excessive exposure.

## Individual protection measures

**Eye/face protection:** Use safety glasses (with side shields). Safety glasses (with side shields) should be consistent with EN 166 or equivalent.

## Skin protection

Hand protection: Use chemical resistant gloves classified under Standard EN374: Protective gloves against chemicals and micro-organisms. Examples of preferred glove barrier materials include: Butyl rubber. Chlorinated polyethylene. Polyethylene. Ethyl vinyl alcohol laminate ("EVAL"). Examples of acceptable glove barrier materials include: Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Viton. Polyvinyl chloride ("PVC" or "vinyl"). When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374) is recommended. When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374) is recommended. Glove thickness alone is not a good indicator of the level of protection a glove provides against a chemical substance as this level of protection is also highly dependent on the specific composition of the material that the glove is fabricated from. The thickness of the glove must, depending on model and type of material, generally be more than 0.35 mm to offer sufficient protection for prolonged and frequent contact with the substance. As an exception to this general rule it is known that multilayer laminate gloves may offer prolonged protection at thicknesses less than 0.35 mm. Other glove materials with a thickness of



Product name: GREAT STUFF PRO™ Gun Foam B1 750ml

Version: 10.0

**Revision Date: 03.11.2016** 

less than 0.35 mm may offer sufficient protection when only brief contact is expected. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

**Other protection:** Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task.

Respiratory protection: Atmospheric levels should be maintained below the exposure guideline. When atmospheric levels may exceed the exposure guideline, use an approved airpurifying respirator equipped with an organic vapor sorbent and a particle filter. For situations where the atmospheric levels may exceed the level for which an air-purifying respirator is effective, use a positive-pressure air-supplying respirator (air line or self-contained breathing apparatus). For emergency response or for situations where the atmospheric level is unknown, use an approved positive-pressure self-contained breathing apparatus or positive-pressure air line with auxiliary self-contained air supply.

Use the following CE approved air-purifying respirator: Organic vapor cartridge with a highly toxic particulate pre-filter, type AP3.

## **Environmental exposure controls**

See SECTION 7: Handling and storage and SECTION 13: Disposal considerations for measures to prevent excessive environmental exposure during use and waste disposal.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

## 9.1 Information on basic physical and chemical properties

**Appearance** 

Physical state Foam
Color Pink
Odor Musty

Odor Threshold No test data available

**pH** Not applicable

Melting point/rangeNo test data availableFreezing pointNo test data availableBoiling point (760 mmHg)No test data available

Flash point closed cup No test data available

Evaporation Rate (Butyl Acetate No test data available

= 1)

Flammability (solid, gas)

Lower explosion limit

Upper explosion limit

No test data available

No test data available

Vapor PressureContainer is under pressure.

Relative Vapor Density (air = 1) No test data available

Relative Density (water = 1) 1.1 - 1.2 at 25 °C / 25 °C Supplier Water solubility insoluble, reacts, evolution of CO2

T: 020 7703 9786

FLINTS
Theatrical Chandle

**Product name: GREAT STUFF PRO™ Gun Foam B1 750ml**Revision Date: 03.11.2016

Version: 10.0

Partition coefficient: n-

octanol/water

No data available

octanol/water

Auto-ignition temperatureNo test data availableDecomposition temperatureNo test data available

Kinematic Viscosity Not applicable Explosive properties Not explosive

Oxidizing properties No

9.2 Other information

Molecular weight Not applicable

NOTE: The physical data presented above are typical values and should not be construed as a specification.

## **SECTION 10: STABILITY AND REACTIVITY**

10.1 Reactivity: No data available

- **10.2 Chemical stability:** Stable under recommended storage conditions. See Storage, Section 7. Unstable at elevated temperatures.
- **10.3 Possibility of hazardous reactions:** Can occur. Exposure to elevated temperatures can cause product to decompose and generate gas. This can cause pressure build-up and/or rupturing of closed containers. Acids.
- **10.4 Conditions to avoid:** Avoid temperatures above 50 °C Elevated temperatures can cause container to vent and/or rupture. Exposure to elevated temperatures can cause product to decompose.
- **10.5 Incompatible materials:** Avoid contact with: Acids. Alcohols. Amines. Ammonia. Bases. Metal compounds. Strong oxidizers. Products based on diisocyanates like TDI and MDI react with many materials to release heat. The reaction rate increases with temperature as well as with increased contact; these reactions can become violent. Contact is increased by stirring or if the other material acts as a solvent. Products based on diisocyanates such as TDI and MDI are not soluble in water and will sink to the bottom, but react slowly at the interface. The reaction forms carbon dioxide gas and a layer of solid polyurea. Reaction with water will generate carbon dioxide and heat.
- **10.6 Hazardous decomposition products:** Decomposition products depend upon temperature, air supply and the presence of other materials. Toxic gases are released during decomposition.

## **SECTION 11: TOXICOLOGICAL INFORMATION**

Toxicological information appears in this section when such data is available.

11.1 Information on toxicological effects
Acute toxicity
Acute oral toxicity

Product name: GREAT STUFF PRO™ Gun Foam B1 750ml

Revision Date: 03.11.2016 Version: 10.0

Low toxicity if swallowed. Small amounts swallowed incidentally as a result of normal handling operations are not likely to cause injury; however, swallowing larger amounts may cause injury. Signs and symptoms of excessive exposure may include: May cause lacrimation (tears). Salivation. Convulsions. Tremors. Increased activity (hyperactivity).

As product: Single dose oral LD50 has not been determined.

Based on information for component(s): LD50, Rat, > 5,000 mg/kg Estimated.

## Acute dermal toxicity

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

As product: The dermal LD50 has not been determined.

Based on information for component(s): LD50, Rabbit, > 2,000 mg/kg Estimated.

## Acute inhalation toxicity

In confined or poorly ventilated areas, vapor can easily accumulate and can cause unconsciousness and death due to displacement of oxygen. Excessive exposure may cause irritation to upper respiratory tract (nose and throat) and lungs. May cause pulmonary edema (fluid in the lungs.) Effects may be delayed. May cause central nervous system depression. Symptoms of excessive exposure may be anesthetic or narcotic effects; dizziness and drowsiness may be observed. Excessive exposure may increase sensitivity to epinephrine and increase myocardial irritability (irregular heartbeats). Decreased lung function has been associated with overexposure to isocyanates.

As product: The LC50 has not been determined.

#### Skin corrosion/irritation

Prolonged contact may cause moderate skin irritation with local redness.

Material may stick to skin causing irritation upon removal.

May stain skin.

## Serious eye damage/eye irritation

May cause moderate eye irritation.

May cause slight temporary corneal injury.

## Sensitization

Skin contact may cause an allergic skin reaction.

Animal studies have shown that skin contact with isocyanates may play a role in respiratory sensitization.

May cause allergic respiratory reaction.

MDI concentrations below the exposure guidelines may cause allergic respiratory reactions in individuals already sensitized.

Asthma-like symptoms may include coughing, difficult breathing and a feeling of tightness in the chest. Occasionally, breathing difficulties may be life threatening.

## **Specific Target Organ Systemic Toxicity (Single Exposure)**

Contains component(s) which are classified as specific target organ toxicant, single exposure, category 3.

**Product name: GREAT STUFF PRO™ Gun Foam B1 750ml** Revision Date: 03.11.2016

Version: 10.0

## **Specific Target Organ Systemic Toxicity (Repeated Exposure)**

Tissue injury in the upper respiratory tract and lungs has been observed in laboratory animals after repeated excessive exposures to MDI/polymeric MDI aerosols.

Contains component(s) which have been reported to cause effects on the following organs in animals: kidney

Liver

## Carcinogenicity

Lung tumors have been observed in laboratory animals exposed to respirable aerosol droplets of MDI/Polymeric MDI (6 mg/m3) for their lifetime. Tumors occurred concurrently with respiratory irritation and lung injury. Current exposure guidelines are expected to protect against these effects reported for MDI.

## **Teratogenicity**

In laboratory animals, MDI/polymeric MDI did not cause birth defects; other fetal effects occurred only at high doses which were toxic to the mother.

## Reproductive toxicity

No relevant data found.

## Mutagenicity

Genetic toxicity data on MDI are inconclusive. MDI was weakly positive in some in vitro studies; other in vitro studies were negative. Animal mutagenicity studies were predominantly negative.

## **Aspiration Hazard**

Based on physical properties, not likely to be an aspiration hazard.

## COMPONENTS INFLUENCING TOXICOLOGY:

## Prepolymer of MDI and polyol

#### Acute inhalation toxicity

For similar material(s): 4,4'-Methylenediphenyl diisocyanate (CAS 101-68-8). LC50, Rat, 1 Hour, Aerosol, 2.24 mg/l

For similar material(s): 2,4'-Diphenylmethane diisocyanate (CAS 5873-54-1). LC50, Rat, 4 Hour, Aerosol, 0.387 mg/l

#### Diphenylmethane Diisocyanate, isomers and homologues

## Acute inhalation toxicity

LC50, Rat, 4 Hour, dust/mist, 0.49 mg/l

For similar material(s): 4,4'-Methylenediphenyl diisocyanate (CAS 101-68-8). LC50, Rat, 1 Hour, Aerosol, 2.24 mg/l

For similar material(s): 2,4'-Diphenylmethane diisocyanate (CAS 5873-54-1). LC50, Rat, 4 Hour, Aerosol, 0.387 mg/l

#### Tris(1-chloro-2-propyl) phosphate

#### Acute inhalation toxicity

No deaths occurred at this concentration. LC50, Rat, 4 Hour, dust/mist, > 7 mg/l

## 4,4'-methylenediphenyl diisocyanate



Version: 10.0

**Product name: GREAT STUFF PRO™ Gun Foam B1 750ml**Revision Date: 03.11.2016

Acute inhalation toxicity

LC50, Rat, 1 Hour, dust/mist, 2.24 mg/l

#### dimethyl ether

Acute inhalation toxicity

LC50, Rat, 4 Hour, gas, 164000 ppm

#### propane

## Acute inhalation toxicity

In confined or poorly ventilated areas, vapor can easily accumulate and can cause unconsciousness and death due to displacement of oxygen. Excessive exposure may increase sensitivity to epinephrine and increase myocardial irritability (irregular heartbeats). May cause central nervous system effects. At air concentrations <1000 ppm, propane exerts very little physiological action; at 100,000 ppm and above it may produce dizziness or other central nervous system effects. Excessive exposure may cause headache, dizziness, anesthesia, drowsiness, unconsciousness and other central nervous system effects, including death. Based on the available data, respiratory irritation was not observed.

LC50, Rat, male and female, 4 Hour, vapour, > 425000 ppm

## **Isobutane**

## Acute inhalation toxicity

LC50, Mouse, 1 Hour, gas, 52 mg/l

## **SECTION 12: ECOLOGICAL INFORMATION**

Ecotoxicological information appears in this section when such data is available.

## 12.1 Toxicity

## Prepolymer of MDI and polyol

## Acute toxicity to fish

Material is not classified as dangerous to aquatic organisms.

## Diphenylmethane Diisocyanate, isomers and homologues

#### Acute toxicity to fish

The measured ecotoxicity is that of the hydrolyzed product, generally under conditions maximizing production of soluble species.

Material is not classified as dangerous to aquatic organisms (LC50/EC50/IC50/LL50/EL50 greater than 100 mg/L in most sensitive species).

Based on information for a similar material:

LC50, Danio rerio (zebra fish), static test, 96 Hour, > 1,000 mg/l, OECD Test Guideline 203 or Equivalent

#### Acute toxicity to aquatic invertebrates

Based on information for a similar material:

EC50, Daphnia magna (Water flea), static test, 24 Hour, > 1,000 mg/l, OECD Test Guideline 202 or Equivalent

## Acute toxicity to algae/aquatic plants

Based on information for a similar material:

Product name: GREAT STUFF PRO™ Gun Foam B1 750ml

**Revision Date: 03.11.2016** Version: 10.0

NOEC, Desmodesmus subspicatus (green algae), static test, 72 Hour, Growth rate inhibition, 1.640 mg/l. OECD Test Guideline 201 or Equivalent

## Toxicity to bacteria

Based on information for a similar material:

EC50, activated sludge, static test, 3 Hour, Respiration rates., > 100 mg/l

## Toxicity to soil-dwelling organisms

EC50, Eisenia fetida (earthworms), Based on information for a similar material:, 14 d, > 1,000 mg/kg

## Toxicity to terrestrial plants

EC50, Avena sativa (oats), Growth inhibition, 1,000 mg/l

EC50, Lactuca sativa (lettuce), Growth inhibition, 1,000 mg/l

## Tris(1-chloro-2-propyl) phosphate

## Acute toxicity to fish

Material is not classified as dangerous to aquatic organisms.

LC50, Lepomis macrochirus (Bluegill sunfish), static test, 96 Hour, 84 mg/l, OECD Test Guideline 203 or Equivalent

## Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), 48 Hour, 131 mg/l

## Acute toxicity to algae/aquatic plants

ErC50, Pseudokirchneriella subcapitata (green algae), static test, 96 Hour, Growth rate inhibition, 82 mg/l, OECD Test Guideline 201 or Equivalent

## Toxicity to bacteria

EC50, activated sludge, Respiration inhibition, 3 Hour, 784 mg/l, OECD 209 Test

#### Chronic toxicity to aquatic invertebrates

NOEC, Daphnia magna (Water flea), semi-static test, 21 d, number of offspring, 32 mg/l MATC (Maximum Acceptable Toxicant Level), Daphnia magna (Water flea), semi-static test, 21 d, number of offspring, > 32 mg/l

## 4,4'-methylenediphenyl diisocyanate

## Acute toxicity to fish

The measured ecotoxicity is that of the hydrolyzed product, generally under conditions maximizing production of soluble species.

Material is not classified as dangerous to aquatic organisms (LC50/EC50/IC50/LL50/EL50 greater than 100 mg/L in most sensitive species).

Based on information for a similar material:

LC50, Danio rerio (zebra fish), static test, 96 Hour, > 1,000 mg/l, OECD Test Guideline 203 or Equivalent

## Acute toxicity to aquatic invertebrates

Based on information for a similar material:

EC50, Daphnia magna (Water flea), static test, 24 Hour, > 1,000 mg/l, OECD Test Guideline 202 or Equivalent

## Acute toxicity to algae/aguatic plants

Based on information for a similar material:

Product name: GREAT STUFF PRO™ Gun Foam B1 750ml Revision Date: 03.11.2016
Version: 10.0

NOEC, Desmodesmus subspicatus (green algae), static test, 72 Hour, Growth rate inhibition, 1,640 mg/l, OECD Test Guideline 201 or Equivalent

## Toxicity to bacteria

Based on information for a similar material:

EC50, activated sludge, static test, 3 Hour, Respiration rates., > 100 mg/l

## Toxicity to soil-dwelling organisms

EC50, Eisenia fetida (earthworms), Based on information for a similar material:, 14 d, > 1,000 mg/kg

## **Toxicity to terrestrial plants**

EC50, Avena sativa (oats), Growth inhibition, 1,000 mg/l EC50, Lactuca sativa (lettuce), Growth inhibition, 1,000 mg/l

#### dimethyl ether

## Acute toxicity to fish

Material is not classified as dangerous to aquatic organisms (LC50/EC50/IC50/LL50/EL50 greater than 100 mg/L in most sensitive species).

LC50, Poecilia reticulata (guppy), semi-static test, 96 Hour, > 4,000 mg/l

## Acute toxicity to aquatic invertebrates

LC50, Daphnia magna (Water flea), 48 Hour, > 4,000 mg/l, OECD Test Guideline 202 or Equivalent

## propane

#### Acute toxicity to fish

Material is not classified as dangerous to aquatic organisms.

## <u>Isobutane</u>

## Acute toxicity to fish

Material is not classified as dangerous to aquatic organisms.

## 12.2 Persistence and degradability

#### Prepolymer of MDI and polyol

**Biodegradability:** Expected to degrade slowly in the environment.

#### Diphenylmethane Diisocyanate, isomers and homologues

**Biodegradability:** In the aquatic and terrestrial environment, material reacts with water forming predominantly insoluble polyureas which appear to be stable. In the atmospheric environment, material is expected to have a short tropospheric half-life, based on calculations and by analogy with related diisocyanates.

10-day Window: Not applicable

Biodegradation: 0 % Exposure time: 28 d

Method: OECD Test Guideline 302C or Equivalent

#### Tris(1-chloro-2-propyl) phosphate

Biodegradability: Material is expected to biodegrade very slowly (in the environment). Fails

to pass OECD/EEC tests for ready biodegradability.

10-day Window: Fail **Biodegradation:** 14 %

T: 020 7703 9786



Product name: GREAT STUFF PRO™ Gun Foam B1 750ml Revision Date: 03.11.2016
Version: 10.0

Exposure time: 28 d

Method: OECD Test Guideline 301E or Equivalent

10-day Window: Not applicable **Biodegradation:** 95 % **Exposure time:** 64 d

Method: OECD Test Guideline 302A or Equivalent

## 4,4'-methylenediphenyl diisocyanate

**Biodegradability:** In the aquatic and terrestrial environment, material reacts with water forming predominantly insoluble polyureas which appear to be stable. In the atmospheric environment, material is expected to have a short tropospheric half-life, based on calculations and by analogy with related diisocyanates.

10-day Window: Not applicable

**Biodegradation:** 0 % **Exposure time:** 28 d

Method: OECD Test Guideline 302C or Equivalent

#### dimethyl ether

Biodegradability: Material is expected to biodegrade very slowly (in the environment). Fails

to pass OECD/EEC tests for ready biodegradability.

10-day Window: Fail **Biodegradation:** 5 % **Exposure time:** 28 d

Method: OECD Test Guideline 301A or Equivalent

#### propane

Biodegradability: No relevant data found.

#### Isobutane

**Biodegradability:** Biodegradation may occur under aerobic conditions (in the presence of oxygen).

## 12.3 Bioaccumulative potential

Bioaccumulation: No data available.

#### 12.4 Mobility in soil

## Prepolymer of MDI and polyol

In the aquatic and terrestrial environment, movement is expected to be limited by its reaction with water forming predominantly insoluble polyureas.

## <u>Diphenylmethane Diisocyanate, isomers and homologues</u>

In the aquatic and terrestrial environment, movement is expected to be limited by its reaction with water forming predominantly insoluble polyureas.

#### Tris(1-chloro-2-propyl) phosphate

Potential for mobility in soil is slight (Koc between 2000 and 5000).

Partition coefficient (Koc): 1300 Estimated.

## 4,4'-methylenediphenyl diisocyanate

In the aquatic and terrestrial environment, movement is expected to be limited by its reaction with water forming predominantly insoluble polyureas.

Product name: GREAT STUFF PRO™ Gun Foam B1 750ml Revision Date: 03.11.2016

Version: 10.0

## dimethyl ether

Potential for mobility in soil is very high (Koc between 0 and 50).

Partition coefficient (Koc): 1.29 - 14 Estimated.

#### propane

Potential for mobility in soil is very high (Koc between 0 and 50).

Partition coefficient (Koc): 24 - 460 Estimated.

#### Isobutane

Potential for mobility in soil is very high (Koc between 0 and 50).

Partition coefficient (Koc): 35 Estimated.

#### 12.5 Results of PBT and vPvB assessment

#### Prepolymer of MDI and polyol

This substance has not been assessed for persistence, bioaccumulation and toxicity (PBT).

## Diphenylmethane Diisocyanate, isomers and homologues

This substance is not considered to be persistent, bioaccumulating and toxic (PBT).

## Tris(1-chloro-2-propyl) phosphate

This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

## 4,4'-methylenediphenyl diisocyanate

This substance is not considered to be persistent, bioaccumulating and toxic (PBT).

## dimethyl ether

This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

#### propane

This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

## Isobutane

This substance is not considered to be persistent, bioaccumulating and toxic (PBT). This substance is not considered to be very persistent and very bioaccumulating (vPvB).

#### 12.6 Other adverse effects

Product contains no ozone-depleting components.

## SECTION 13: DISPOSAL CONSIDERATIONS

## 13.1 Waste treatment methods

Contents under pressure. Do not puncture or incinerate container. Relieve all pressure prior to disposal. DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. Any disposal practice must be in compliance with all local and national laws and regulations. The generation of waste should be avoided or minimized wherever possible. Refer to manufacturer/supplier for information on recovery/recycling.



**Product name: GREAT STUFF PRO™ Gun Foam B1 750ml**Revision Date: 03.11.2016

Version: 10.0

The definitive assignment of this material to the appropriate EWC group and thus its proper EWC code will depend on the use that is made of this material. Contact the authorized waste disposal services.

## **SECTION 14: TRANSPORT INFORMATION**

## Classification for ROAD and Rail transport (ADR/RID):

**14.1 UN number** UN 1950

14.2 UN proper shipping name AEROSOLS

14.3 Transport hazard class(es) 2.1

**14.4 Packing group** Not applicable

**14.5** Environmental hazards Not considered environmentally hazardous based on

available data.

14.6 Special precautions for user No data available.

## **Classification for SEA transport (IMO-IMDG):**

**14.1 UN number** UN 1950

14.2 UN proper shipping name AEROSOLS

14.3 Transport hazard class(es) 2.1

**14.4 Packing group** Not applicable

**14.5** Environmental hazards Not considered as marine pollutant based on available data.

14.6 Special precautions for user EmS: F-D, S-U

14.7 Transport in bulk according

to Annex I or II of MARPOL 73/78 and the IBC or IGC

Code

Consult IMO regulations before transporting ocean bulk

#### Classification for AIR transport (IATA/ICAO):

**14.1 UN number** UN 1950

**14.2 UN proper shipping name** Aerosols, flammable

14.3 Transport hazard class(es) 2.1

14.4 Packing group Not applicable
14.5 Environmental hazards Not applicable
14.6 Special precautions for user No data available.

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

Product name: GREAT STUFF PRO™ Gun Foam B1 750ml

Version: 10.0

**Revision Date: 03.11.2016** 

## **SECTION 15: REGULATORY INFORMATION**

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

## REACh Regulation (EC) No 1907/2006

This product contains only components that have been either pre-registered, registered, are exempt from registration, are regarded as registered or are not subject to registration according to Regulation (EC) No. 1907/2006 (REACH)., The aforementioned indications of the REACH registration status are provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. It is the buyer 's/user's responsibility to ensure that his/her understanding of the regulatory status of this product is correct.

## Restrictions on the manufacture, placing on the market and use:

The following substance/s contained in this product is/are subject through Annex XVII of REACH regulation to restrictions on the manufacture, placing on the market and use when present in certain dangerous substances, mixtures and articles. Users of this product have to comply with the restrictions placed upon it by the aforementioned provision.

CAS-No.: 9016-87-9	Name: Diphenylmethane Diisocyanate, isomers and		
	homologues		
Restriction status: listed in REACH Annex XVII			
Restricted uses: See Annex XVII to Regulation (EC) no 1907/2006 for Conditions of restriction			
CAS-No.: 101-68-8	Name: 4,4'-methylenediphenyl diisocyanate		
Restriction status: listed in REACH Annex XVII			
Restricted uses: See Annex XVII to Regulation (EC) no 1907/2006 for Conditions of restriction			
CAS-No.: 75-28-5	Name: Isobutane		

Restriction status: listed in REACH Annex XVII

Restricted uses: See Annex XVII to Regulation (EC) no 1907/2006 for Conditions of restriction

# Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Listed in Regulation: FLAMMABLE AEROSOLS

Number in Regulation: P3a

150 t 500 t

#### 15.2 Chemical safety assessment

Not applicable

## **SECTION 16: OTHER INFORMATION**

#### Full text of H-Statements referred to under sections 2 and 3.

H220 Extremely flammable gas. H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.



Product name: GREAT STUFF PRO™ Gun Foam B1 750ml Revision Date: 03.11.2016
Version: 10.0

H280 Contains gas under pressure; may explode if heated. H302 Harmful if swallowed. H315 Causes skin irritation. H317 May cause an allergic skin reaction. Causes serious eye irritation. H319 H332 Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. H334 H335 May cause respiratory irritation. Suspected of causing cancer. H351 H373 May cause damage to organs through prolonged or repeated exposure.

# Classification and procedure used to derive the classification for mixtures according to Regulation (EC) No 1272/2008

Aerosol - 1 - H222 - On basis of test data. Skin Irrit. - 2 - H315 - Calculation method Eye Irrit. - 2 - H319 - Calculation method Resp. Sens. - 1 - H334 - Calculation method Skin Sens. - 1 - H317 - Calculation method Carc. - 2 - H351 - Calculation method STOT SE - 3 - H335 - On basis of test data. STOT RE - 2 - H373 - Calculation method

#### Revision

Identification Number: 101197927 / A279 / Issue Date: 03.11.2016 / Version: 10.0

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

Legend

_0g0a	
2000/39/EC	Europe. Commission Directive 2000/39/EC establishing a first list of indicative
	occupational exposure limit values
ACGIH	USA. American Conference of Governmental Industrial Hygienists (ACGIH)
	Threshold Limit Values (TLV)
Asphyxiant	Asphyxiant
Dow IHG	Dow Industrial Hygiene Guideline
GB EH40	UK. EH40 WEL - Workplace Exposure Limits
SEN	Sensitizer
STEL	Short term exposure limit
TWA	Time weighted average
US WEEL	USA. Workplace Environmental Exposure Levels (WEEL)

#### **Information Source and References**

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

DOW CHEMICAL COMPANY LIMITED urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here



**Product name: GREAT STUFF PRO™ Gun Foam B1 750ml**Revision Date: 03.11.2016

Version: 10.0

pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.