BUILDING TRUST



SAFETY DATA SHEET

PINKGRIP

Page: 1

Compilation date: 9/3/15

Revision No: 8

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: PINKGRIP

Product code: PINKGRIP

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC1: Adhesives, sealants.

1.3. Details of the supplier of the safety data sheet

Company name:	EVERBUILD BUILDING PRODUCTS LTD
	SITE 41, KNOWSTHORPE WAY
	CROSS GREEN INDUSTRIAL ESTATE
	LEEDS
	WEST YORKSHIRE
	LS9OSW
	ENGLAND
Tel:	0044 113 240 3456
Fax:	0044 113 240 0024
Email:	sds@everbuild.co.uk
	hau

1.4. Emergency telephone number

Emergency tel:	0044 113 240 3456 (office hours only)
Manufacturer:	EVERBUILD BUILDING PRODUCTS LTD
	Site 41
	Knowsthorpe Way, Cross Green Industrial Estate
	Leeds
	West Yorkshire
	LS9 0SW
	United Kingdom
	Tel: (0044) 113 240 3456
	Fax: (0044) 113 240 0024
	Emergency tel: (0044) 113 240 3456
	Email: sds@everbuild.co.uk

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: F+: R12; -: R52/53; -: R67

Classification under CLP: Aquatic Chronic 3: H412; Eye Irrit. 2: H319; Flam. Liq. 1: H224; Skin Irrit. 2: H315



SAFETY DATA SHEET

PINKGRIP

Most important adverse effects:	Extremely flammable. Harmful to aquatic organisms, may cause long-term adverse
	effects in the aquatic environment. Vapours may cause drowsiness and dizziness.
2.2. Label elements	
Label elements under CLP:	
Hazard statements:	H224: Extremely flammable liquid and vapour.
	H315: Causes skin irritation.
	H319: Causes serious eye irritation.
	H412: Harmful to aquatic life with long lasting effects.
Signal words:	Danger
Hazard pictograms:	GHS02: Flame
	GHS07: Exclamation mark
Procentionany statements	P102: Keen out of reach of children
Frecautionary statements.	P102: Keep out of reach of children.
	P403+235: Store in a well-ventilated place. Keep cool. P501: Dispose of contents to hazardous waste.
	P332+313: If skin irritation occurs: Get medical advice.
	P242: Use only non-sparking tools.
	P362: Take off contaminated clothing and wash before reuse.
	P337+313: If eye irritation persists: Get medical advice/attention.
	P321: Specific treatment (see information on this label).
	P302+352: IF ON SKIN: Wash with plenty of soap and water.
	P103: Read label before use.
	P243: Take precautionary measures against static discharge.
	P264: Wash hands thoroughly after handling.
	P280: Wear protective gloves / eye protection.
	P273: Avoid release to the environment.
	P210: Keep away from heat/sparks/open flames/hot surfaces No smoking.
	P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove
	contact lenses, if present and easy to do. Continue rinsing.
	P370+378: In case of fire: Use chemical powder, foam or carbon dioxide for extinction.
Label elements under CHIP:	
Hazard symbols:	Extremely flammable.

Risk phrases: R12: Extremely flammable.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R67: Vapours may cause drowsiness and dizziness.



SAFETY DATA SHEET

PINKGRIP

Safety phrases:S2: Keep out of the reach of children.S43: In case of fire, use dry chemical powder, foam or carbon dioxide.S9: Keep container in a well-ventilated place.S16: Keep away from sources of ignition - No smoking.S29: Do not empty into drains.

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

ETHYL ACETATE - REACH registered number(s): 01-2119475103-46-XXXX

EINECS	CAS	CHIP Classification	CLP Classification	Percent
205-500-4	141-78-6	F: R11; Xi: R36; -: R66; -: R67	Flam. Liq. 2: H225; Eye Irrit. 2: H319;	10-30%
			STOT SE 3: H336; -: EUH066	

NAPHTHA (PETROLEUM) HYDROTREATED LIGHT

265-151-9	64742-49-0	F: R11; Xi: R38; N: R51/53; Xn:	Flam. Liq. 2: H225; Aquatic Chronic 2:	1-10%
		R65; -: R66; -: R67	H411; Skin Irrit. 2: H315; STOT SE 3:	
			H336; Asp. Tox. 1: H304	

NAPHTHA (PETROLEUM), SOLVENT-REFINED LIGHT - REACH registered number(s): 01-2119473851-33-XXXX

920-750-0	-	F: R11; Xi: R38; N: R51/53; Xn:	Flam. Liq. 2: H225; Aquatic Chronic 2:	1-10%
		R65; -: R66; -: R67	H411; Skin Irrit. 2: H315; STOT SE 3:	
			H336; Asp. Tox. 1: H304	

HYDROCARBONS, C9-C12, N-ALKANES, ISOALKANES, CYCLICS, AROMATICS (2-25%)

919-446-0	-	-: R10; Xn: R48/20; N: R51/53; Xn: R65; -: R66; -: R67	Flam. Liq. 3: H226; Aquatic Chronic 2: H411; STOT SE 3: H336; Asp. Tox. 1:	<1%
			H304; STOT RE 1: H372; -: EUH066	

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact:	Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash
	immediately with plenty of soap and water.
Eye contact:	Bathe the eye with running water for 15 minutes. Consult a doctor.
Ingestion:	Do not induce vomiting. If conscious, give half a litre of water to drink immediately.
	Consult a doctor.
Inhalation:	Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a
	doctor.



SAFETY DATA SHEET

PINKGRIP

Page: 4

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: There may be a feeling of tightness in the chest with shortness of breath.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.

Vapour may travel considerable distance to source of ignition and flash back.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Eliminate all sources of

ignition.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Do not use equipment in clean-up procedure which may produce sparks. Absorb into dry earth or sand.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Smoking is forbidden. Use non-sparking tools. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.



SAFETY DATA SHEET

PINKGRIP

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Keep away from

sources of ignition. Prevent the build up of electrostatic charge in the immediate area.

Ensure lighting and electrical equipment are not a source of ignition.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

ETHYL ACETATE

Workplace exposure limits:

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
EU	200ppm	400ppm	-	-

Respirable dust

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures:	Ensure there is sufficient ventilation of the area. Ensure lighting and electrical
	equipment are not a source of ignition.
Respiratory protection:	Respiratory protection not required. If ventilation is insufficient, suitable respiratory
	protection must be provided. Gas/vapour filter, type A: organic vapours (EN141).
Hand protection:	Protective gloves. Natural rubber gloves are recommended, neoprene are acceptable.
Eye protection:	Safety glasses. Ensure eye bath is to hand.
Skin protection:	Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State:PasteColour:PinkOdour:PETROL-LIKEEvaporation rate:FastSolubility in wate:InsolubleViscosity:Highly viscousFlash point°C:-10Relative density: ~1.25VOC g/l:378



SAFETY DATA SHEET

PINKGRIP

Page: 6

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

ETHYL ACETATE

DERMAL	RBT	LD50	>20000	mg/kg
ORAL	RAT	LD50	6100	mg/kg
ORAL	RBT	LD50	4934	mg/kg
VAPOURS	RAT	4H LC50	29.3	ppmV

Toxicity values: No data available.

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: There may be a feeling of tightness in the chest with shortness of breath.

Section 12: Ecological information



SAFETY DATA SHEET

PINKGRIP

12.1. Toxicity

Hazardous ingredients:

ETHYL ACETATE

Daphnia magna	48H EC50	3090	mg/l
Pimephales promelas (Fat-head Minnow)	96H LC50	230	mg/l

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Harmful to aquatic organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

Waste code number: 08 04 09

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1133

14.2. UN proper shipping name

Shipping name: ADHESIVES

(ETHYL ACETATE)

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: III



Marine pollutant: No

SAFETY DATA SHEET

PINKGRIP

Page: 8

14.5. Environmental hazards

Environmentally hazardous: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No
	453/2010.
	* indicates text in the SDS which has changed since the last revision.
Phrases used in s.2 and s.3:	EUH066: Repeated exposure may cause skin dryness or cracking.
	H224: Extremely flammable liquid and vapour.
	H225: Highly flammable liquid and vapour.
	H226: Flammable liquid and vapour.
	H304: May be fatal if swallowed and enters airways.
	H315: Causes skin irritation.
	H319: Causes serious eye irritation.
	H336: May cause drowsiness or dizziness.
	H372: Causes damage to organs <or affected,="" all="" if="" known="" organs="" state=""> through</or>
	prolonged or repeated exposure <state conclusively="" exposure="" if="" is="" it="" of="" proven="" route="" th="" that<=""></state>
	no other routes of exposure cause the hazard>.
	H411: Toxic to aquatic life with long lasting effects.
	H412: Harmful to aquatic life with long lasting effects.
	R10: Flammable.
	R11: Highly flammable.
	R12: Extremely flammable.
	R36: Irritating to eyes.
	R38: Irritating to skin.
	R48/20: Harmful: danger of serious damage to health by prolonged exposure through
	inhalation.
	R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic
	environment.
	R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the



SAFETY DATA SHEET

PINKGRIP

	aquatic environment.
	R65: Harmful: may cause lung damage if swallowed.
	R66: Repeated exposure may cause skin dryness or cracking.
	R67: Vapours may cause drowsiness and dizziness.
Legend to abbreviations:	PNEC = predicted no effect level
	DNEL = derived no effect level
	LD50 = median lethal dose
	LC50 = median lethal concentration
	EC50 = median effective concentration
	IC50 = median inhibitory concentration
	dw = dry weight
	bw = body weight
	cc = closed cup
	oc = open cup
	MUS = mouse
	GPG = guinea pig
	RBT = rabbit
	HAM = hamster
	HMN = human
	MAM = mammal
	PGN = pigeon
	IVN = intravenous
	SCU = subcutaneous
	SKN = skin
	DRM = dermal
	OCC = ocular/corneal
	PCP = phycico-chemical properties
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive
	and shall be used only as a guide. This company shall not be held liable for any
	damage resulting from handling or from contact with the above product.