

STANDARD THINNERS/GUN WASH



Compilation date: 13/06/2005

**Revision date:** 12/05/2017

Revision No: 2

Page: 1

# Section 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product name: STANDARD THINNERS/GUN WASH

Product code: 45-802-5430

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Used as a thinner/solvent.

### 1.3. Details of the supplier of the safety data sheet

Company name: JOHN MYLAND LIMITED

26 ROTHSCHILD STREET

WEST NORWOOD

LONDON SE27 0HQ

Tel: 020 8670 9161

Fax: 020 8761 5700

Email: info@mylands.co.uk

## 1.4. Emergency telephone number

Emergency tel: 020 8670 9161 (OFFICE HOURS ONLY)

## **Section 2: Hazards identification**

### 2.1. Classification of the substance or mixture

Classification under CLP: Flam. Liq. 2: H225; Eye Irrit. 2: H319; Repr. 2: H361d; Skin Irrit. 2: H315; STOT RE 2:

H373; STOT SE 3: H336; -: EUH066

Most important adverse effects: Repeated exposure may cause skin dryness or cracking. Highly flammable liquid and

vapour. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of damaging the unborn child. May cause damage to organs

through prolonged or repeated exposure.

# 2.2. Label elements

### Label elements:

Hazard statements: EUH066: Repeated exposure may cause skin dryness or cracking.

H225: Highly flammable liquid and vapour.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

H361d: Suspected of damaging the unborn child.

H373: May cause damage to organs through prolonged or repeated exposure.



#### STANDARD THINNERS/GUN WASH

Page: 2

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark GHS08: Health hazard







Signal words: Danger

Precautionary statements: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P241: Use explosion-proof electrical/ventilating/lighting/... equipment.

P260: Do not breathe dust/fumes/gas/mist/vapours/spray.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352: IF ON SKIN: Wash with plenty of water.

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water.

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for

breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

#### 2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

# Section 3: Composition/information on ingredients

## 3.2. Mixtures

## **Hazardous ingredients:**

# ETHYL ACETATE

| EINECS    | CAS      | PBT / WEL | CLP Classification  | Percent |
|-----------|----------|-----------|---|---------|
| 205-500-4 | 141-78-6 | -         | Flam. Liq. 2: H225; Eye Irrit. 2: H319;<br>STOT SE 3: H336; -: EUH066 | 10-30%  |

### **TOLUENE**

| 203-625-9 | 108-88-3 | - | Flam. Liq. 2: H225; Repr. 2: H361d;  | 10-30% |
|-----------|----------|---|--------------------------------------|--------|
|           |          |   | Asp. Tox. 1: H304; STOT RE 2: H373;  |        |
|           |          |   | Skin Irrit. 2: H315; STOT SE 3: H336 |        |



#### STANDARD THINNERS/GUN WASH

Page: 3

| NI DI | ITVI | ACE: | $\Gamma \wedge T \Gamma$ | - |
|-------|------|------|--------------------------|---|
| וע-טנ | IIII | ALLE | ІАІГ                     | - |

| 204-658-1   | 123-86-4  | -  | Flam. Liq. 3: H226; STOT SE 3: H336; -: EUH066                        | 10-30% |
|-------------|-----------|--|---|--------|
| XYLENE SOL  | VENT      |  |   |        |
| 215-535-7   | 1330-20-7 | -  | Skin Irrit. 2: H315; Acute Tox. 4:<br>H312+H332; Flam. Liq. 3: H226   | 10-30% |
| ETHYL METH  | YL KETONE |  |   |        |
| 201-159-0   | 78-93-3   | -  | Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336; -: EUH066    | 10-30% |
| PROPYL ACE  | TATE      |  |   |        |
| 203-686-1   | 109-60-4  | -  | Flam. Liq. 2: H225; Eye Irrit. 2: H319;<br>STOT SE 3: H336; -: EUH066 | 1-10%  |
| ETHANOL     |           |  |   |        |
| 200-578-6   | 64-17-5   | Substance with a Community workplace exposure limit. | Flam. Liq. 2: H225  | 1-10%  |
| ACETONE     |           |  |   |        |
| 200-662-2   | 67-64-1   | -  | Flam. Liq. 2: H225; Eye Irrit. 2: H319;<br>STOT SE 3: H336; -: EUH066 | 1-10%  |
| ISOPROPYL A | ACETATE   |  |   |        |
| 203-561-1   | 108-21-4  | -  | Flam. Liq. 2: H225; Eye Irrit. 2: H319;<br>STOT SE 3: H336; -: EUH066 | 1-10%  |

#### Section 4: First aid measures

# 4.1. Description of first aid measures

**Skin contact:** Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist

examination.

Ingestion: Wash out mouth with water.

Inhalation: Not applicable.

## 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe

pain. The vision may become blurred. May cause permanent damage.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach

pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.



#### STANDARD THINNERS/GUN WASH

Page: 4

## 4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

### Section 5: Fire-fighting measures

### 5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

#### 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

#### Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Mark out the contaminated area with signs and prevent access to unauthorised

personnel. Do not attempt to take action without suitable protective clothing - see section

8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

# 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

### 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method.

### 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

## Section 7: Handling and storage

#### 7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Avoid the formation or spread of mists in the air.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

### 7.3. Specific end use(s)

Specific end use(s): No data available.

# Section 8: Exposure controls/personal protection



### STANDARD THINNERS/GUN WASH

Page: 5

## 8.1. Control parameters

### **Hazardous ingredients:**

### **ETHYL ACETATE**

## Respirable dust

| State        | 8 hour TWA | 15 min. STEL | 8 hour TWA | 15 min. STEL |
|--------------|------------|--------------|------------|--------------|
| UK           | 400ppm     | No std       | -          |              |
| OLUENE       |            |              |            |              |
| UK           | 191 mg/m3  | 574 mg/m3    | -          |              |
| N-BUTYL ACET | ATE        |              |            |              |
| UK           | 724 mg/m3  | 966 mg/m3    | -          |              |
| KYLENE SOLVI | ENT        |              |            |              |
| UK           | 220 mg/m3  | 441 mg/m3    | -          |              |
| ETHYL METHY  | L KETONE   |              |            |              |
| UK           | 600 mg/m3  | 899 mg/m3    | -          |              |
| PROPYL ACET  | ATE        |              |            |              |
| UK           | 849 mg/m3  | 1060 mg/m3   | -          |              |
| ACETONE      |            |              | ·          |              |
| UK           | 1210 mg/m3 | 3620 mg/m3   | -          |              |
| SOPROPYL AC  | CETATE     |              | ,          |              |
|              |            |              |            |              |

849 mg/m3

# **DNEL/PNEC Values**

UK

**DNEL / PNEC** No data available.

420 mg/m3

# 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

**Eye protection:** Tightly fitting safety goggles. Ensure eye bath is to hand.

Skin protection: Protective clothing.

# Section 9: Physical and chemical properties

# 9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Colourless

Odour: Perceptible odour

Flash point°C: 12 VOC g/I: 850



#### STANDARD THINNERS/GUN WASH

Page: 6

### 9.2. Other information

Other information: No data available.

## Section 10: Stability and reactivity

### 10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

## 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

#### 10.4. Conditions to avoid

Conditions to avoid: Heat.

## 10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

## 10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

# **Section 11: Toxicological information**

# 11.1. Information on toxicological effects

### Hazardous ingredients:

## **ETHYL ACETATE**

| ORL | MUS | LD50 | 4100 | mg/kg |
|-----|-----|------|------|-------|
| ORL | RAT | LD50 | 5620 | mg/kg |
| SCU | RAT | LDLO | 5    | gm/kg |

## **TOLUENE**

| IVN | RAT | LD50 | 1960 | mg/kg |
|-----|-----|------|------|-------|
| ORL | MUS | LD50 | 2    | gm/kg |
| ORL | RAT | LD50 | 6900 | mg/kg |

#### **N-BUTYL ACETATE**

| ORL   RAT   LD50   10768   mg/kg |
|----------------------------------|
|----------------------------------|



### STANDARD THINNERS/GUN WASH

Page: 7

#### **PROPYL ACETATE**

| ORL | MUS | LD50 | 8300 | mg/kg |
|-----|-----|------|------|-------|
| ORL | RAT | LD50 | 9370 | mg/kg |

### **ETHANOL**

| IVN | RAT | LD50 | 1440 | mg/kg |
|-----|-----|------|------|-------|
| ORL | MUS | LD50 | 3450 | mg/kg |
| ORL | RAT | LD50 | 7060 | mg/kg |

#### **ACETONE**

| ORL | MUS | LD50 | 3    | gm/kg |
|-----|-----|------|------|-------|
| ORL | RAT | LD50 | 5500 | mg/kg |

### **ISOPROPYL ACETATE**

| IVN | RAT | LDLO | 174  | mg/kg |
|-----|-----|------|------|-------|
| ORL | RAT | LD50 | 6750 | mg/kg |

## Relevant hazards for product:

| •                             |       |                       |
|-------------------------------|-------|-----------------------|
| Hazard                        | Route | Basis                 |
| Skin corrosion/irritation     | DRM   | Hazardous: calculated |
| Serious eye damage/irritation | OPT   | Hazardous: calculated |
| Reproductive toxicity         |       | Hazardous: calculated |
| STOT-single exposure          | -     | Hazardous: calculated |
| STOT-repeated exposure        | -     | Hazardous: calculated |

# Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe

pain. The vision may become blurred. May cause permanent damage.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach

pain may occur.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

# Section 12: Ecological information

# 12.1. Toxicity



### STANDARD THINNERS/GUN WASH

Page: 8

Hazardous ingredients:

**ACETONE** 

BLUEGILL (Lepomis macrochirus) LC50 8300 mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

**NB:** The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

**Section 14: Transport information** 

14.1. UN number

UN number: UN1263

14.2. UN proper shipping name

Shipping name: PAINT RELATED MATERIAL

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: II

14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E



#### STANDARD THINNERS/GUN WASH

Page: 9

Transport category: 2

# Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

## 15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

### **Section 16: Other information**

#### Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

2015/830.

\* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.

H225: Highly flammable liquid and vapour.

H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H312+H332: Harmful in contact with skin or if inhaled

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

H361d: Suspected of damaging the unborn child.

H373: May cause damage to organs ({{{0|||message=<or state all organs affected, if known>|||filter=(\_)?ORGAN\_.+}})) through prolonged or repeated exposure ({{{1||| message=<state route of exposure if it is conclusively proven that no other routes of

exposure cause the hazard>|||filter=(\_)?EXP\_ROUTE\_.+}}}).

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.