



SAFETY DATA SHEET RYLARD BRASS LACQUER

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name RYLARD BRASS LACQUER

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses PC 9a: Coatings and paints, thinners, paint removers.

Uses advised against Keep away from food, drink and animal feeding stuffs.

1.3. Details of the supplier of the safety data sheet

Supplier Axalta Coating Systems Huthwaite UK Ltd
Blackwell Road
Huthwaite
Nottinghamshire
NG17 2RL
Tel: +44 (0)1623 510585

Contact person info-huthwaite@axaltacs.com

1.4. Emergency telephone number

Emergency telephone +44 (0)1623 528938 (Not 24 Hours)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 2 - H225

Health hazards Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319

Environmental hazards Not Classified

2.2. Label elements

Pictogram



Signal word Danger

Hazard statements H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.

RYLARD BRASS LACQUER

Precautionary statements	<p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P261 Avoid breathing vapour/ spray.</p> <p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P271 Use only outdoors or in a well-ventilated area.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.</p> <p>P403+P235 Store in a well-ventilated place. Keep cool.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>
---------------------------------	--

Contains XYLENE, ETHYLBENZENE

Other information

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

XYLENE 30-60%		
CAS number: 1330-20-7	EC number: 215-535-7	REACH registration number: 01-2119488216-32-0000
Classification	Classification (67/548/EEC or 1999/45/EC)	
Flam. Liq. 3 - H226	R10 Xn;R20/21 Xi;R38	
Acute Tox. 4 - H312		
Acute Tox. 4 - H332		
Skin Irrit. 2 - H315		
Asp. Tox. 1 - H304		
2-METHOXY-1-METHYLETHYL ACETATE 10-30%		
CAS number: 108-65-6	EC number: 203-603-9	REACH registration number: 01-2119475791-29-0000
Classification	Classification (67/548/EEC or 1999/45/EC)	
Flam. Liq. 3 - H226	R10 Xi;R36	
BUTANONE 5-10%		
CAS number: 78-93-3	EC number: 201-159-0	REACH registration number: 01-2119457290-43-0000
Classification	Classification (67/548/EEC or 1999/45/EC)	
Flam. Liq. 2 - H225	F;R11 Xi;R36 R66 R67	
Eye Irrit. 2 - H319		
STOT SE 3 - H336		

RYLARD BRASS LACQUER

ETHYLBENZENE		5-10%
CAS number: 100-41-4	EC number: 202-849-4	REACH registration number: 01-2119489370-35-0000
Classification Flam. Liq. 2 - H225 Acute Tox. 4 - H332 Asp. Tox. 1 - H304	Classification (67/548/EEC or 1999/45/EC) F;R11 Xn;R20	

PROPAN-2-OL		1-5%
CAS number: 67-63-0	EC number: 200-661-7	REACH registration number: 01-2119457558-25-0000
Classification Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336	Classification (67/548/EEC or 1999/45/EC) F;R11 Xi;R36 R67	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move affected person to fresh air at once. Get medical attention if any discomfort continues.
Ingestion	Rinse mouth thoroughly with water. Do not induce vomiting. Get medical attention immediately. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs.
Skin contact	Remove contaminated clothing. Rinse immediately with plenty of water. Get medical attention if any discomfort continues.
Eye contact	Remove any contact lenses and open eyelids wide apart. Rinse with water. Continue to rinse for at least 15 minutes. Get medical attention promptly if symptoms occur after washing.

4.2. Most important symptoms and effects, both acute and delayed

General information Effects may be delayed. Keep affected person under observation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with the following media: Foam, carbon dioxide or dry powder. Dry chemicals, sand, dolomite etc.

5.2. Special hazards arising from the substance or mixture

Specific hazards The product is highly flammable. In case of fire, toxic gases may be formed. Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m³.

Hazardous combustion products Toxic gases or vapours. Oxides of carbon.

5.3. Advice for firefighters

RYLARD BRASS LACQUER

Protective actions during firefighting	Move containers from fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

For non-emergency personnel Keep unnecessary and unprotected personnel away from the area.

6.2. Environmental precautions

Environmental precautions Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Keep combustible materials away from spillage. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into containers.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Keep away from heat, sparks and open flame. Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep away from oxidising materials, heat and flames. Store in tightly-closed, original container in a dry, cool and well-ventilated place. Keep only in the original container. Avoid contact with oxidising agents.

Storage class Flammable liquid storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

XYLENE

Long-term exposure limit (8-hour TWA): WEL 50 ppm(Sk) 220 mg/m3(Sk)

Short-term exposure limit (15-minute): WEL 100 ppm(Sk) 441 mg/m3(Sk)

2-METHOXY-1-METHYLETHYL ACETATE

Long-term exposure limit (8-hour TWA): WEL 50 ppm(Sk) 274 mg/m3(Sk)

Short-term exposure limit (15-minute): WEL 100 ppm(Sk) 548 mg/m3(Sk)

BUTANONE

Long-term exposure limit (8-hour TWA): WEL 200 ppm(Sk) 600 mg/m3(Sk)

Short-term exposure limit (15-minute): WEL 300 ppm(Sk) 899 mg/m3(Sk)

RYLARD BRASS LACQUER

ETHYLBENZENE

Long-term exposure limit (8-hour TWA): WEL 100 ppm(Sk) 441 mg/m³(Sk)

Short-term exposure limit (15-minute): WEL 125 ppm(Sk) 552 mg/m³(Sk)

PROPAN-2-OL

Long-term exposure limit (8-hour TWA): WEL 400 ppm 999 mg/m³

Short-term exposure limit (15-minute): WEL 500 ppm 1250 mg/m³

WEL = Workplace Exposure Limit

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients. All handling should only take place in well-ventilated areas.

Eye/face protection

If a risk assessment indicates eye contact is possible, suitable eye protection should be worn e.g. safety spectacles, safety goggles or a faceshield as appropriate. Personal protective equipment for eye and face protection should comply with European Standard EN166.

Hand protection

Wear protective gloves. To protect hands from chemicals, gloves should comply with European Standard EN374. Gloves made from the following material may provide suitable chemical protection: Nitrile rubber; thickness 0.35mm minimum. Butyl / Viton® (>0.70mm) or PVA. Butyl Rubber; thickness 0.5mm minimum. Fluorinated rubber (Viton); thickness 0.4mm minimum. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Glove thickness is not necessarily a good measure of glove resistance as the permeation rate will depend on the exact glove composition. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of skin contact.

Hygiene measures

Provide eyewash station. Do not smoke in work area. Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

Respiratory protection

Wear a respirator fitted with the following cartridge: Organic vapour filter.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Clear liquid.
Colour	Water-white.
Odour	Characteristic.
Initial boiling point and range	79 - 81°C @ 013 hPa
Flash point	5°C Closed cup.
Upper/lower flammability or explosive limits	Lower flammable/explosive limit: 7 g/m ³

RYLARD BRASS LACQUER

Vapour pressure Not available.

Relative density 0.92 @ 23°C

Partition coefficient Not available.

9.2. Other information

Other information No additional information

Volatile organic compound This product contains a maximum VOC content of 780 g/l.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability No particular stability concerns.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Not determined.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid contact with strong oxidising agents.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects This product is toxic.

Acute toxicity - dermal

ATE dermal (mg/kg) 2,444.44

Acute toxicity - inhalation

ATE inhalation (gases ppm) 9,000.0

ATE inhalation (vapours mg/l) 22.0

ATE inhalation (dusts/mists mg/l) 3.0

General information Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

Inhalation Gas or vapour in high concentrations may irritate the respiratory system. Symptoms following overexposure may include the following: Coughing. Harmful by inhalation.

Ingestion Gastrointestinal symptoms, including upset stomach.

Skin contact Harmful in contact with skin. Irritating to skin.

RYLARD BRASS LACQUER

Eye contact Irritating to eyes. Symptoms following overexposure may include the following: Redness.

SECTION 12: Ecological Information

Ecotoxicity The product components are not classified as environmentally hazardous. However, large or frequent spills may have hazardous effects on the environment.

12.1. Toxicity

Toxicity Avoid release to the environment.

12.2. Persistence and degradability

Persistence and degradability No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not available.

12.4. Mobility in soil

Mobility The product hardens to a solid, immobile substance.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment No data available.

12.6. Other adverse effects

Other adverse effects Not determined.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste should be treated as controlled waste.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1263

UN No. (IMDG) 1263

UN No. (ICAO) 1263

UN No. (ADN) 1263

14.2. UN proper shipping name

Proper shipping name (ADR/RID) PAINT

Proper shipping name (IMDG) PAINT

Proper shipping name (ICAO) PAINT

Proper shipping name (ADN) PAINT

14.3. Transport hazard class(es)

ADR/RID class 3

RYLARD BRASS LACQUER

ADR/RID classification code	F1
ADR/RID label	3
IMDG class	3
ICAO class/division	3
ADN class	3

Transport labels



14.4. Packing group

ADR/RID packing group	II
IMDG packing group	II
ADN packing group	II
ICAO packing group	II

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

EmS	F-E, S-E
ADR transport category	2
Emergency Action Code	•3YE
Hazard Identification Number (ADR/RID)	33
Tunnel restriction code	(D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
----------------	--

Guidance	Workplace Exposure Limits EH40.
----------	---------------------------------

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

RYLARD BRASS LACQUER

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet	<p>WEL: Workplace Exposure Limit. ATE: Acute Toxicity Estimate. CAS: Chemical Abstracts Service. DNEL: Derived No Effect Level. DMEL: Derived Minimal Effect Level. PNEC: Predicted No Effect Concentration. PBT: Persistent, Bioaccumulative and Toxic substance. vPvB: Very Persistent and Very Bioaccumulative.</p>
Revision comments	Product name change.
Revision date	18/10/2018
Revision	2
Supersedes date	04/10/2016
SDS number	32147
Risk phrases in full	<p>R10 Flammable. R11 Highly flammable. R20 Harmful by inhalation. R20/21 Harmful by inhalation and in contact with skin. R36 Irritating to eyes. R36/38 Irritating to eyes and skin. R38 Irritating to skin. R66 Repeated exposure may cause skin dryness or cracking. R67 Vapours may cause drowsiness and dizziness.</p>
Hazard statements in full	<p>H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H315 Causes skin irritation. H319 Causes serious eye irritation. H332 Harmful if inhaled. H336 May cause drowsiness or dizziness.</p>

The information of this SDS is based on the present state of our knowledge and meets the requirements of EU and national laws. The user's working conditions however, are beyond our knowledge and control. The product is not to be used for purposes other than those specified under section 1 without a written permission. It remains the responsibility of the user to ensure that the necessary steps are taken to meet the laws and regulations. Handling of the product may only be done by people above 18 years of age, who are satisfactorily informed of how to do the work, the hazardous properties and necessary safety precautions. The information given in this SDS is to describe the product only in terms of health and safety requirements and should not, therefore, be construed as guaranteeing specific properties.