



Page 1/9

Fax: 0049-(0)7223-284-245

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.06.2017 Version number 13 Revision: 02.06.2017

# SECTION 1: Identification of the substance/mixture and of the company undertaking

- · 1.1 Product identifier
- Trade name: UHU all purpose gel
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Adhesives
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

UHU GmbH & Co.KG

Herrmannstraße 7

D-77815 Bühl (Baden)

Tel.:0049-(0)7223-284-0

email: info@uhu.boltongroup.de

- · Further information obtainable from: UHU QESH
- · 1.4 Emergency telephone number:

Tel.: + 49 (0) 30/19240 (Notruf) Tel.: + 49 (0) 72 23/28 40

#### **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



STOT SE 3 H336 May cause drowsiness or dizziness.

- 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02 GHS07

- · Signal word Danger
- Hazard-determining components of labelling: methyl acetate
- · Hazard statements

H225 Highly flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

**Precautionary statements** 

P101 If medical advice is needed, have product container or label at hand.

(Contd. on page 2)





Page 2/9

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.06.2017 Version number 13 Revision: 02.06.2017

Trade name: UHU all purpose gel

(Contd. of page 1)

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing vapours.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

### **SECTION 3: Composition/information on ingredients**

- · 3.2 Mixtures
- · **Description**: Adhesive

· Dangerous components:				
CAS: 79-20-9	methyl acetate	25-50%		
EINECS: 201-185-2 Reg.nr.: 01-2119459211-47-XXXX	♠ Flam. Liq. 2, H225; ♦ Eye Irrit. 2, H319; STOT SE 3, H336			
CAS: 64-17-5 EINECS: 200-578-6 Reg.nr.: 01-2119457610-43	ethanol Flam. Liq. 2, H225	25-50%		

Additional information: For the wording of the listed hazard phrases refer to section 16.

#### **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eve contact:

Rinse opened eye for several minutes under running water. Then consult a doctor.

- After swallowing: Do not induce vomiting; call for medical help immediately.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

• 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

#### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from the substance or mixture

No further relevant information available.

(Contd. on page 3)





Page 3/9

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.06.2017 Version number 13 Revision: 02.06.2017

Trade name: UHU all purpose gel

(Contd. of page 2)

- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

#### **SECTION 6: Accidental release measures**

- 6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Send for recovery or disposal in suitable receptacles.

Ensure adequate ventilation.

Pick up mechanically.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

### **SECTION 8: Exposure controls/personal protection**

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

### 79-20-9 methyl acetate

WEL Short-term value: 770 mg/m³, 250 ppm Long-term value: 616 mg/m³, 200 ppm

(Contd. on page 4)





Page 4/9

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.06.2017 Version number 13 Revision: 02.06.2017

Trade name: UHU all purpose gel

	(Contd. of page 3)					
64-17-5 ethanol						
g-term value: 1920 mg/m³, 1000 ppm						
ethyl acetate						
Verbraucher, Verschlucken Langzeitige Exposition	44 mg/kg bw/day (.)					
Verbraucher, Hautkontakt Langzeitiege Exposition	44 mg/kg bw/day (.)					
Verbraucher, Einatmen Langzeitige Exposition	131 mg/m³ (.)					
hanol						
Verbraucher, Verschlucken Langzeitige Exposition	87 mg/kg bw/day (.)					
Verbraucher, Hautkontakt Langzeitiege Exposition	206 mg/kg bw/day (.)					
Verbraucher, Akute Wirkungen, Einatmen	950 mg/m³ (.)					
Verbraucher, Einatmen Langzeitige Exposition	114 mg/m³ (.)					
79-20-9 methyl acetate						
Süßwasser   0.12 mg/l (.)						
Meerwasser 0.012 mg/l (.)						
hanol						
Süßwasser   0.96 mg/l (.)						
Meerwasser 0.79 mg/l (.)						
	ethyl acetate Verbraucher, Verschlucken Langzeitige Exposition Verbraucher, Hautkontakt Langzeitige Exposition Verbraucher, Einatmen Langzeitige Exposition Verbraucher, Verschlucken Langzeitige Exposition Verbraucher, Verschlucken Langzeitige Exposition Verbraucher, Hautkontakt Langzeitige Exposition Verbraucher, Akute Wirkungen, Einatmen Verbraucher, Einatmen Langzeitige Exposition  ethyl acetate r   0.12 mg/l (.) er   0.012 mg/l (.) hanol r   0.96 mg/l (.)					

- Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Do not inhale gases / fumes / aerosols.

Avoid direct contact with the chemical/ the product/ the preparation by organisational measures.

- Respiratory protection: Not required.
- · Protection of hands:

Solvent resistant gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Not required.

GB-EN

(Contd. on page 5)





Page 5/9

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.06.2017 Version number 13 Revision: 02.06.2017

Trade name: UHU all purpose gel

(Contd. of page 4)

GB-EN

9.1 Information on basic physical and	chamical proportios
General Information	chemical properties
Appearance:	
Form:	Fluid
Colour:	Colourless
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	: 57 °C
Flash point:	-10 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	425 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Explosion limits:	
Lower:	3.1 Vol %
Upper:	16.0 Vol %
Vapour pressure at 20 °C:	220 hPa
Density at 20 °C:	0.95 g/cm <sup>3</sup>
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Fully miscible.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic at 20 °C:	90000 mPas
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	68.8 %
Water:	0.4 %
VOC (EC)	68.85 %
Solids content:	30.8 %





Page 6/9

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.06.2017 Version number 13 Revision: 02.06.2017

Trade name: UHU all purpose gel

(Contd. of page 5)

9.2 Other information

All relevant physical data were determined for the mixture. All non determined data are not measurably or not relevant for the characterization of the mixture.

## **SECTION 10: Stability and reactivity**

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

### **SECTION 11: Toxicological information**

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 v	· LD/LC50 values relevant for classification:			
79-20-9 m	79-20-9 methyl acetate			
Oral	LD50	3705 mg/kg (rabbit)		
64-17-5 et	64-17-5 ethanol			
Oral	LD50	7060 mg/kg (rat)		
Inhalative	LC50/4 h	20000 mg/l (rat)		

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

### **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.

(Contd. on page 7)





Page 7/9

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.06.2017 Version number 13 Revision: 02.06.2017

Trade name: UHU all purpose gel

(Contd. of page 6)

- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow product to reach ground water, water course or sewage system.

- 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

### **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

· European waste catalogue

08 04 09\* waste adhesives and sealants containing organic solvents or other hazardous substances

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

# **SECTION 14: Transport information**

· 14.1	UN	-Number	
--------	----	---------	--

· ADR, IMDG, IATA UN1133

· 14.2 UN proper shipping name

· **ADR** 1133 ADHESIVES

1133 KLEBSTOFFE, Sondervorschrift 640H

· IMDG, IATA ADHESIVES

- · 14.3 Transport hazard class(es)
- · ADR, IMDG, IATA



· Class 3 Flammable liquids.

· Label 3

· 14.4 Packing group

· ADR

· IMDG, IATA

· 14.5 Environmental hazards:

· Marine pollutant: No

(Contd. on page 8)





Page 8/9

(Contd. of page 7)

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.06.2017 Version number 13 Revision: 02.06.2017

Trade name: UHU all purpose gel

· 14.6 Special precautions for user Warning: Flammable liquids. -

• EMS Number: F-E,S-D
• Stowage Category B

· 14.7 Transport in bulk according to Annex II

of Marpol and the IBC Code Not applicable.

· Transport/Additional information:

· ADR

Limited quantities (LQ)Excepted quantities (EQ)5LCode: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000

· Transport category 3 · Tunnel restriction code E

·IMDG

Limited quantities (LQ)Excepted quantities (EQ)Code: E2

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

· UN "Model Regulation": UN 1133 ADHESIVES, 3, III

### **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### Relevant phrases

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Department issuing SDS: UHU QESH

(Contd. on page 9)





Page 9/9

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.06.2017 Version number 13 Revision: 02.06.2017

Trade name: UHU all purpose gel

(Contd. of page 8)

· Contact:

Frau A. Liar, Herr Dr. C. Hanf

· Abbreviations and acronyms:

Flam. Liq. 2: Flammable liquids – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

\* Data compared to the previous version altered.

GB-EN -