

new



Festool Tools

Flints decided that we just had to stock Festool Equipment. We have used their equipment and quite honestly, it is the best. The extra price you pay is amply rewarded not only by the longevity of the tools [Three year guarantee!] but by their working efficiency. I have personally found Festool sanders to work twice as effectively as anything else I have tried. To put it another way, a job that was going to take four days only takes two. You soon see how the extra expenditure begins to pay dividends. But there's more, Festool equipment is renowned for keeping dust to a minimum so your working environment becomes safer. Our big problem with Festool tools is that they are packed with so many features that we are finding it impossible to squeeze them into the four catalogue pages we allocated to the range!

Visit flints.co.uk for more Festool tools and seasonal offers!

FESTOOL CORDLESS DRILLS

new



Drives
630 Spax 5x40
screws on one
charge!!!

T 15+3 Series For those who require and appreciate the ultimate cordless driver. Brushless EC-TEC motor with integrated motor management for long service life and the highest output. Impressive ergonomics: Compact, lightweight and perfectly balanced. Fully electron torque setting and switch-off for precise screwdriving.

The
ultimate drill from
Festool!

Switchover from screwdriving to drilling without changing the set torque. FastFix interface for all FastFix attachments and CENTROTEC rapid tool-change system. Latest Lithium-ion battery technology for the longest sustained usage

Battery voltage: 14.4 V. Idling speed, 1st gear/2nd gear: 0-450/0-1500 min-1. Drilling diameter: wood/steel 35/16 mm. Torque adjustment: 0.5-8/0.5-6 Nm. Max. torque: wood/steel 27/40 Nm. Chuck range: 1.5-13 mm. Battery: Li-Ion 3.0 Ah. Charging time: Li-Ion 45 min. Weight with Li-Ion: 1,5 kg.

☐ Supplied in a Systainer Case with: charger TRC 3, CENTROTEC tool chuck, CENTROTEC wood drill bit D4, CENTROTEC bit holder, FastFix keyless chuck 13 mm, bit PZ 2, FastFix angle attachment, FastFix eccentric attachment, spare battery pack Li-Ion 3.0 Ah.

T 15+3	code	price
T 15+3 Drill set with attachments listed above	FES564388	£450.00
T 15+3 As above but excluding angle and eccentric att	FES564384	£372.00
T 12+3 Drill with attachments - see flints.co.uk for info	FES564380	£429.00



Festool Attachable Drill Lamp

Lamp	code	price
Attachable drill lamp fits the above T15 +3	FES496927	£22.10



C 12 Li 1,5 Set GB

Superior efficiency and supreme build quality for driving large quantities of screws with very impressive ergonomics. This drill will drill at right angles and hard against upstands!

✓ Latest Lithium-ion battery technology for the longest sustained usage ✓ Fastfix interface for rapid changing of heads. ✓ Supplied with Fastfix eccentric attachment allowing

screws to be driven tight against upstands. ✓ Supplied with right angle chuck for very tight access. ✓ Hex bits can be placed directly into drill head with no chuck at all for tight spaces!

✓ Supplied with 13mm keyless chuck. ✓ Supplied in Systainer Container system. ✓ 42 torque settings. ✓ Spare battery and charger. ✓ Centrotec bit holder. ✓ Three Year Guarantee!

Very highly recommended!

Battery voltage: 10.8V. Idling speed, 1st gear/2nd gear: 0-450/0-1500 min, Max drilling diameter, wood/steel: 25/14mm. Torque setting range, 1st gear: 2-7Nm. Torque adjustment: 0.5-8/0.5-6 Nm. Max. torque, wood/steel: 20/34 Nm. Chuck range: 1.5-13mm. Li-Ion battery capacity 1.5 Ah. Charging time Li-Ion 20min, Weight with Li-Ion battery 1.3kg.

☐ Supplied in a Systainer box complete with TRC 3 charger, CENTROTEC tool chuck, wood drill bit D4 CENTROTEC, CENTROTEC bit holder, FastFix keyless chuck 13mm, bit PZ 2, FastFix angle attachment, FastFix eccentric attachment, spare battery pack.

C 12 CE-MH45-Set GB	code	price
C 12 Drill set with attachments	FES564365	£412.00

Festool Drilling and Driving Accessories



☛ **21 Piece Drill and Holder Set** This set contains Festool drill holders from 3-6.5mm plus a set of spare bits and allen key. Designed for very rapid interchanging of drills.



☛ **Countersink with depth stop** Total control for best quality work.



☛ **Hook Driver** Latches into cup hooks etc.



☛ **De-burring Countersink** Removes the burr from tubes from 2-8mm.



☛ **Fast Fix Depth Stop** Allows you to define the depth to drive a screw head.

Festool Drilling and driving accessories	code	price
21 Piece Drill & Holder Set	FES493420	£62.97
Drill Countersink with depth stop [3.5mm]	FES492523	£39.10
Drill Countersink with depth stop [4.5mm]	FES492524	£41.20
Hook Driver [for driving cup hooks]	FES492526	£7.90
Deburring Countersink [2-8 mm]	FES492520	£20.70
Deburring Countersink [5-15mm]	FES492521	£25.70
Depth Stop Fastfix	FES493539	£73.90



JIGSAWS



PS 300EQ-Plus GB [and PSB]

Festool quality with a choice of handle types. ✓ Patented three-way saw blade guide for cutting precise angles ✓ High-quality drive components give longer service life. ✓ Great value. ✓ Improved

splinterguard, no reworking. ✓ Perfectly balanced for effortless one-handed operation. ✓ FastFix rapid-change system for easy saw blade changes. ✓ Brilliant cutting power (MMC electronics) Power consumption: 720W. Stroke rate: 1000-2900min⁻¹ ± Pendulum cover adjustment in stages: 4. Inclination: 0-45°. Cutting depth in wood: 120mm. Cutting depth in NF metals : 20mm. Cutting depth in steel (soft): 10mm. Weight: 2,4kg. Power supply: 240V.

☐ Complete in a Systainer with two blades and splinterguard.

PS [PSB] 300 EQ-Plus GB	code	price
Jigsaw PS	FES561450	£207.00
Jigsaw PSB [Top Handle]	FES561459	£207.00
Guide Rail Adapter	FES490031	£10.20
Parallel Fence	FES490119	£18.60
Splinter Guard	FES490120	£4.40

DOMINO JOINTING SYSTEM

new



The DOMINO jointing system An essential component in wooden jointing.

✓ More versatile: suitable both for panel joints and jointing frames and racks.

✓ More stable: the special shape and large surface area for gluing on the DOMINO dowel ensure maximum stability.

✓ Quicker: the first dowel hole is aligned with extreme ease and routed accurately using stop pins. It secures the joined work pieces immediately, accurately and flush with the edge.

✓ The system also tolerates smaller inaccuracies in adjacent dowel holes, allowing you to work even more quickly and easily.

DOMINO Biscuit Jointer DF 500 Q-Plus GB



As unique as the system: the DOMINO jointer combines exceptional versatility with simple handling and maximum precision.

✓ Efficient extraction. Extracts up to 95% of chips generated.

✓ Depth stop. Quick, precise adjustment for five different depths.

✓ Routing height adjuster with scale. Simple and precise routing.

✓ Movable stepped stop. Height adjuster for central hole in material thicknesses: 16, 20, 22, 25, 28, 40mm.

✓ Retractable stop pins. For quick and precise positioning of the first DOMINO dowel on both work pieces.

✓ Refined technology. High-quality, robust inner mechanism for consistently accurate routing results.

✓ Patented principle. Route long holes in an instant thanks to the simultaneous turning and oscillating movement. No kickbacks.

✓ Hole width selection. Easy to adjust while the biscuit jointer is operating: fixed long hole (1) or with clearance (2).

DF 500 Q-Plus GB	code	price
Domino Biscuit Jointer	FES574429	£615.00
Domino Assortment Box	FES498899	£154.95

PLUNGE SAWS



Hugely popular!

TS55 EBQ Plus-FS GB A truly fantastic circular saw offering very precise cutting in materials up to 55mm thick. Perfect for cutting ply tops to size or doors to length using the guide rail. Use it for making expansion joints in swollen timber floor-

ing. This saw will provide splinter free very high-quality results.

✓ FastFix: quick and easy saw blade changing and adaptation to the working material.

✓ Spring-loaded spacer wedge for unhindered plunge cuts.

✓ Attachable splinterguard for high-quality working results.

✓ Quick-acting brake system for safe, convenient sawing.

✓ Tool-less play setting on the guide rail.

✓ Very popular, best selling saw.

Power consumption: 1200W. Idle engine speed: 2000-5200 min⁻¹ ±. Saw blade diameter: 160mm. Inclination: 0-45°. Cutting depth: 0-55mm. Cutting depth at 45°: 43mm. Cutting depth at 90°/45°: 0-43/0-55 mm. Connection Ø d/e: 27/36mm. Weight 4,5kg.

☐ Supplied in Systainer Box complete with fine tooth blade, guide rail, splinterguard and operation tool

TS55 EBQ-Plus-FS-GB	code	price
Circular Saw	FES561515	£395.00
Fine Tooth Blade 160mm Ø	FES491952	£53.40
Panther Saw Blade 160mm Ø	FES496301	£39.40
Splinter Guard	FES491473	£9.50
Guide Rail (1400mm)	FES491498	£64.00
Connecting piece	FES482107	£11.40
Parallel Fence	FES491469	£32.30

TS75 EBQ-Plus-FS GB



Another winner from Festool with all the features of the TS55 but with more power delivering an increased cutting depth of 75mm. Ideal for cutting through multiple boards in one pass.

Power consumption: 1600W.

Idle engine speed: 1350-3550min⁻¹ ±. Saw blade diameter : 210mm. Cutting depth: 0-75mm. Cutting depth at 45°: 55mm. Cutting depth at 90°/45°: 0-55/0-75mm. Inclination: 0-47°. Connection Ø d/e: 27/36mm. Weight 6,2kg.

☐ Supplied in Systainer Box complete with fine tooth blade, guide rail, and splinter guard.

TS75 EBQ-Plus-FS-GB	code	price
Circular Saw	FES561441	£485.00
Fine Tooth Blade 210mm Ø	FES493199	£75.80
Universal Saw Blade 210mm Ø	FES493198	£58.10
Panther Saw Blade 210mm Ø	FES493196	£56.20
Splinter Guard	FES491473	£9.50
Parallel Fence	FES490119	£18.60
Guide Rail (1400mm)	FES491498	£64.00
Connecting piece	FES482107	£10.80
Gecko Dosh Set [see page 3.61]	FES493507	£59.20

SLIDING COMPOUND MITRE SAW

new



KS 120 EB GB 240v Set Finally a sliding compound mitre saw that combines a large cutting capacity with a compact lightweight design that achieves the precision needed for high-quality results and detailed solutions to inspire any professional user. Absolutely packed with unique features. Including-

- ✓ **Variable speed pre-selection** Smooth start up, safety brake and overload protection. Special electronics

adapt the machine performance to the working material.

- ✓ **Precision dual-line laser.** The dual laser lines will always show the exact cut whether viewed from left or right.

- ✓ **Fast Fix rapid blade changing system.**

- ✓ **Convenient operation** The guard release is integrated in the two-stage switch and can be operated by both right and left-handers. The same applies for the safety switch-on lock.

- ✓ **Dust extraction** The KAPEX is fitted with an extraction connector and an efficient chip deflector funnel: the chips are extracted directly where they are produced.

- ✓ **Accurate Settings** Fine adjuster operated from the front, for precise cutting angles. Make complex cuts in no time at all.

- ✓ **Precision grooving** Cut accurate grooves with the stepless trenching depth adjuster: simply actuate the lever, set the trenching depth with a single turn and start working.

- ✓ **120mm cutting depth** The unique special cutting position on the KAPEX allows you to cut strip material with a maximum height of 120mm quickly, safely and accurately.

- ✓ **Intelligent base height** The saw base is the same height as the SYSTAINER SYS 1, which can be used to support long workpieces when working on the floor.

Power consumption: 1600W. Idle engine speed: 1400-3400rpm. Saw blade diameter : 260mm. Inclination angle: 47-47°. Mitre angle: 50°/60°. Cutting depth at 90°/ 90°: 305x88mm. Cutting depth at 45°/ 90°: 215x88mm. Cutting depth at 45°/ 45°[left] : 215x55mm. Cutting depth at 45°/ 45°[right]: 215x35mm. Special cutting depth at 45°/ 90°[right]: 20x120mm. Crown moulding diagonal cut 168mm 0-43/0-55 mm. Connection Ø d/e: 27/36mm. Dimensions: 713x500x470mm. Weight: 21.5kg.

□ **Complete with:** HW Universal saw blade, bevel, workpiece clamp, multifunction table MFT 800 basic, 2x table extensions, 2x Crown moulding stops, clamping set, operating tool.

KS 120 EB GB 240v Set	code	price
Sliding Compound Mitre saw	FES561291	£1,541.00
Universal Saw Blade 260mm Ø	FES494604	£107.90
Fine tooth Saw Blade 260mm Ø	FES494605	£129.40

SANDING



Deltex Mini Corner Sander The DELTEX is the perfect tool for efficient material removal over small surfaces with corners and edges: handy shape and powerful thanks to its gear mechanism, it is

perfect for one-handed operation. Sheet size 93mm▲

[Visit flints.co.uk for genuine Festool abrasives].

DX 93 E-Plus GB 240V	code	price
Deltex Mini Sander	FES567858	£217.00



DTS 400 EQ-Plus GB

Triangle-shaped sanding pad for efficient sanding of corners and other awkward spots. Significant time saving and less reworking. The enclosed dustproof bearing and extremely tear-resistant MPE sanding pad ensure a long service life and maximum economic efficiency.

Effective integral turbo dust extractor. Small, lightweight and extremely handy for non-tiring work.

Power consumption: 200W. Speed: 6000-14000 min ±. No. of strokes 12000-28000min ±. Sanding stroke: 2mm. Interchangeable sanding pad: 100x150mm. Connection Ø d/e : 27mm. Weight 1,1kg.

□ **Supplied in a Systainer Box with a sanding pad StickFix 100x150mm, a StickFix abrasive sheet and a filter cartridge.**

DTS 400 EQ-Plus GB	code	price
Delta Triangular Sander	FES567872	£225.00



Sander Polisher RO 150/125 FEQ-Plus GB 240v

I have used the 125mm version of this machine since its introduction and I can't praise it too highly. There is a choice between a course sanding motion for very rapid stock

A personal favourite!

removal and a fine sanding motion for superb finishes. The 150mm version is even more powerful but a little heavier. These machines will pay back their cost many times in efficiency savings.

- ✓ Coarse sanding, fine sanding, and polishing!

- ✓ ROTEX rotary motion for efficient material removal.

- ✓ Eccentric motion for high-quality, scratch-free surfaces.

- ✓ FastFix sanding pad system, quick and tool-less.

- ✓ Ideal ergonomic grip positions.

- ✓ Sanding up to the edge thanks to the Festool PROTECTOR.

- ✓ Virtually no dust [when connected to a Festool extractor].

Rotex 150/125: Power consumption: 720/500W. ROTEX rotary motion speed: 320-660/300-600 min ±. Eccentric motion speed: 3300-6800/3000-6000min ±. Sanding stroke: 5/3,6mm. FastFix sanding pad Ø: 150/125mm. Connection Ø d/e: 27mm. Weight: 2,3/1,9kg. Power supply: 240V.

□ **Supplied in Systainer Box with Sanding pad StickFix Ø 150 /125mm (soft HT), 1x abrasive Brilliant, P 120, Festool PROTECTOR.**

RO 150 [125] FEQ-Plus GB 240v	code	price
150mm Geared Eccentric Sander	FES571808	£425.00
125mm Geared Eccentric Sander	FES571784	£346.00



Sander Polisher ETS 150/3 EQ-Plus GB

3mm sanding stroke for an excellent surface finish. Perfect for final sanding on paintwork, wood and plastic. Weighs only 1.8kg for effortless work. Sanding pad brake for safe faultless work.

Power consumption: 310W. Speed: 4000-10000 min ±. Sanding stroke: 3mm. Interchangeable sanding pad Ø: 150mm. Connection Ø d/e: 27mm.

ETS 150/3 EQ-Plus GB 240v	code	price
150mm Eccentric Sander	FES571792	£265.00

Sanding and Polishing Accessories

150/125mm Polishing Sponge coarse	FES493845/493843	£11.00/£7.20
150/125mm Polishing Sponge fine	FES493866/493864	£11.00/£9.00
150mm Polishing Felt [soft]	FES485972	£6.50
125mm Polishing Felt [soft]	FES493077	pack of 5 £20.00
150/125mm Sanding Pad [hard]	FES496150/492127	£38.50/£27.10
150/125mm Sanding Pad	FES496148/492125	£38.50/£27.10

PLANER



EHL 65 E-Plus 240V GB

- ✓ Low weight and perfectly balanced for non-tiring work. ✓ Compact design, ergonomic handle, low operating noise.
- ✓ Spiral blade for a smooth planing pattern. ✓ Efficient

dust extraction at the left/right side no clean-up needed. ✓ Quick blade changes

Power consumption: 720W. Rotational speed: 15600 min⁻¹. Planing width: 65mm. Planing depth: 0-4mm. Max. rebate depth: 23mm. Connection Ø d/e: 27mm. Noise at idling speed: 76 dB(A). Weight: 2.4kg.

☐ Supplied in Systainer box with parallel fence and tool.

EHL 65 E-Plus 240V GB	code	price
One handed +Planer	FES574547	£213.00
Planer Blades	FES488503	£11.60
Spiral Blade	FES484515	£18.60

ROUTER



OF 1400 EBQ Plus GB

- ✓ Robust and reliable thanks to the dual-bearing cutter spindle.
- ✓ Special base runner with extension and chip deflector to guide the router accurately along edges [accessory]. ✓ MMC electronics for adaptation to the working material.

✓ Ergonomically arranged control elements for safe routing. Power consumption: 1400W. Idle engine speed: 10000-22500 min⁻¹. Routing depth adjustment range: 70mm. Fine height adjustment range: 8mm. Connection Ø d/e: 27/36mm. Weight: 4.5kg. Power supply: 240V. Mains frequency: 50 Hz.

☐ Supplied in a Systainer Box complete with Ø 8 mm clamping collet, Ø 12 mm clamping collet, parallel side fence with fine adjustment and extraction hood, copy ring Ø 30 mm, extraction hood, top, chip deflector and operation tool.

OF 1400 EBQ-Plus GB	code	price
Router	FES574345	£441.00
Guide Rail Adapter	FES492601	£42.60
Copying Ring [24mm]	FES492183	£12.60
Copying Ring [27mm]	FES492184	£12.60
Routing Template	FES492611	£271.10

See page 3.15 for router bits.

MOBILE DUST EXTRACTION



Make a noticeable difference to your working environment by connecting your Festool power tools to a Festool dust extractor. Also ideal for final clean up operations.



CTL 26 E SG GB 240V

- ✓ Approved for dust category L.
- ✓ Antistatic function prevents static developing during work.
- ✓ Infinitely variable suction power adjustment. ✓ Locking brake to prevent from rolling away. ✓ Attachment of SYSTAINERS via Sys-Dock. ✓ Hose holder available as standard for greater

tidiness and safety. ✓ Full utilisation of the filter bag in the container for maximum economic efficiency. ✓ Container volume of 22 litres ✓ Integral automatic electronic switch-on/shut-off for extraction from electric power tools ✓ Suitable for both wet and dry extraction Power consumption: 350-1200W. Airflow max: 3800 l/min. Max. vacuum: 23000Pa. Filter surface area: 14000 cm². Rubber-insulated mains cable: 7.5m. Container/Filter bag capacity: 26L. Dimension (LxWxH): 625x380x550mm. Max. appliance socket connected load: 2400W. Weight: 13 kg.

☐ Supplied in a carton with 1 fitted filter bag, suction hose Ø 27 mm x 3,5 m-AS and hose holder.

CTL 26 E SG GB 240v	code	price
Dust Extractor GL26	FES583499	£404.00
Filter Bag	FES452970	£29.10
Longlife Filter Sack	FES456737	£115.38



CTL MIDI GB 240V All the features of the CTL 22 but with 15L capacity.

Power consumption: 400-1200W. Airflow max.: 2800 L/min. Max. vacuum: 20000Pa. Filter surface area: 5000 cm². Rubber-insulated mains cable: 7,5m. Container/Filter bag capacity: 15/12,5L. Dimension (LxWxH): 440x340x470mm. Max. appliance socket connected load: 2400W. Weight: 9,7kg

☐ Supplied in a carton with 1 fitted filter bag, 1 spare filter bag in the storage compartment and 1 suction hose, dia. 27x3.5 m-AS with angle rotating adapter on the extractor side.

CTL MIDI GB 240v	code	price
Midi Dust Extractor	FES583374	£291.00
Filter Bag	FES494105	£17.40
Compact Cleaning Set	FES497697	£50.30

SYSTAINER SYSTEM



SYS 1 Box



SYS 3-SORT/6



SYS HWZ



SYS 4



Roll board

Visit flints.co.uk for more!

Systainer System Festool Tools are normally supplied in a systainer box. The ingenious system allows boxes to lock together or lock to a rolling base board. You can, for instance buy a sander, a Midi dust extractor, and a Sortainer 6 to hold your abrasives and they will all lock together as one neat unit. Sorted!

Systainer System	dims[lxwxh,mm]	features	code	price
SYS-HWZ	395x295x315	timber tool organiser	FES497658	£106.70
SYS-1 Box	395x295x 105	plastic tray inserts	FES497694	£53.50
SYS 3-SORT/4	395x295x 210	2xS, 1xM, 1xL drawers	FES491522	£90.70
SYS 3-SORT/6	395x295x 210	6 medium drawers	FES491984	£96.00
SYS 4	395x295x315	deep box	FES497566	£48.20
RB SYS 1-5	395x295	roll board 50kg cap. Braked	FES492388	£42.70