






**RAVE**

- *Hardwearing, heterogenous reversible sheet flooring*
- *Colors - Black , Grey, White, Tan*

**SPECIFICATION**

 2.0mm .08 in	 N/A
 N/A	 2m x up to 20m 6.56ft x up to 65ft
	 1.90kg/m2 3.5 lbs/yd2

**RAVE**

**HETEROGENOUS**

**PERFORMANCE AND PROPERTIES**

 **GENERAL PERFORMANCE**  
EN 651



 **ACOUSTIC IMPACT SOUND REDUCTION**  
ISO 717-2 19dB

 **SLIP RESISTANCE**  
AS/NZS 4856 R9  
DIN 51130 R9

 **REACTION TO FIRE**  
EN 13501-1 **Class Cfl-s1**

 **RESISTANCE TO CHEMICALS**  
EN 423 (ASTM F 1303-99)  
Excellent chemical resistance

 **LIGHT FASTNESS**  
EN 20105-B02 (Method 3) ≥6

 **ABRASION RESISTANCE**  
EN 649 Group T


 **INDENTATION - RESIDUAL**  
EN 433 <0.2mm


 **DIMENSIONAL STABILITY**  
EN 434 0.2


 **FLEXIBILITY**  
EN 435 (Method A) Pass


 **VOC EMISSIONS**  
No Solvents Used

 **THERMAL CONDUCTIVITY**  
N/A

 **HYGIENE**  
Contains antimicrobial agents for improved hygiene protection. This product has been independently tested and results demonstrate that it inhibits the growth of MRSA. An effective cleaning regime is however, the most important defence against infection.

 **ELECTRICAL BEHAVIOUR (body voltage)**  
EN1815 This product does not accumulate static charges above 2kV and is classified as 'antistatic'.

 **APPLICATIONS**  
Ballet, Modern, Jazz, Call for percussive use

 For information regarding handling and installation, adhesives, maintenance, applications and chemical resistance, call 800-523-0960

