

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2015/830

• TRUSTED QUALITY SINCE 1921 •  
**RUST-OLEUM®**

# SAFETY DATA SHEET

Magnetic Chalkboard Paint

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : Magnetic Chalkboard Paint  
**Product description** : Paint.  
**Product type** : Liquid.

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses	
Industrial uses Consumer uses Professional uses	
Uses advised against	Reason
None identified.	-

### 1.3 Details of the supplier of the safety data sheet

Rust-Oleum Europe - Martin Mathys NV, Kolenbergstraat 23, B-3545 Zelem, Belgium  
 Telephone no.: +32 (0) 13 460 200  
 Fax no.: +32 (0) 13 460 201

**e-mail address of person responsible for this SDS** : rpmeurohas@ro-m.com

### 1.4 Emergency telephone number

#### Supplier

**Telephone number** : +44 (0) 207 858 1228  
**Hours of operation** : 24 / 7

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mixture

**Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]**

Flam. Liq. 3, H226  
 Aquatic Chronic 4, H413

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

**Hazard pictograms** :



**Signal word** : Warning

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2015/830

Magnetic Chalkboard Paint

## SECTION 2: Hazards identification

- Hazard statements** : Flammable liquid and vapour.  
May cause long lasting harmful effects to aquatic life.
- Precautionary statements**
- General** : P102 - Keep out of reach of children.  
P103 - Read label before use.  
P101 - If medical advice is needed, have product container or label at hand.
- Prevention** : P210 - Keep away from heat, sparks, open flames and hot surfaces. - No smoking.  
P273 - Avoid release to the environment.
- Response** : P303 - IF ON SKIN (or hair):  
P361 - Take off immediately all contaminated clothing.  
P353 - Rinse skin with water or shower.
- Storage** : P403 - Store in a well-ventilated place.  
P235 - Keep cool.
- Disposal** : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.  
Not applicable.
- Supplemental label elements** : Repeated exposure may cause skin dryness or cracking.
- Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.
- Special packaging requirements**
- Containers to be fitted with child-resistant fastenings** : Not applicable.
- Tactile warning of danger** : Not applicable.

### 2.3 Other hazards

- Other hazards which do not result in classification** : None known.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification Regulation (EC) No. 1272/2008 [CLP]	Type
Alkanes, C9-12-iso-	REACH #: 01-2119471991-29 EC: 923-037-2 CAS: 90622-57-4	≥10 - ≤25	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 4, H413 EUH066	[1] [2]
1-isopropyl-2,2-dimethyltrimethylene diisobutyrate	REACH #: 01-2119451093-47 EC: 229-934-9 CAS: 6846-50-0	≤3	Aquatic Chronic 3, H412  <b>See Section 16 for the full text of the H statements declared above.</b>	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2015/830

Magnetic Chalkboard Paint

## SECTION 3: Composition/information on ingredients

- [1] Substance classified with a health or environmental hazard  
 [2] Substance with a workplace exposure limit  
 [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII  
 [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII  
 [5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- General** : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
- Eye contact** : Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

### 4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

### Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:  
 irritation  
 dryness  
 cracking
- Ingestion** : No specific data.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2015/830

Magnetic Chalkboard Paint

## SECTION 4: First aid measures

See toxicological information (Section 11)

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

**Suitable extinguishing media** : Recommended: alcohol-resistant foam, CO<sub>2</sub>, powders, water spray.

**Unsuitable extinguishing media** : Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

**Hazards from the substance or mixture** : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required. Cool closed containers exposed to fire with water.

**Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
metal oxide/oxides

### 5.3 Advice for firefighters

**Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

**Additional information** : No unusual hazard if involved in a fire.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

**For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

### 6.3 Methods and material for containment and cleaning up

**Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2015/830

Magnetic Chalkboard Paint

## SECTION 6: Accidental release measures

- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.
- 6.4 Reference to other sections** : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance.

- 7.1 Precautions for safe handling** : Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the occupational exposure limits. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Operators should wear antistatic footwear and clothing and floors should be of the conducting type. Keep away from heat, sparks and flame. No sparking tools should be used. Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this mixture. Avoid inhalation of dust from sanding. Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Put on appropriate personal protective equipment (see Section 8). Never use pressure to empty. Container is not a pressure vessel. Always keep in containers made from the same material as the original one. Comply with the health and safety at work laws. Do not allow to enter drains or watercourses.
- Information on fire and explosion protection**  
Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations.

#### Notes on joint storage

Keep away from: oxidising agents, strong alkalis, strong acids.

#### Additional information on storage conditions

Observe label precautions. Do not store above the following temperature: 35°C (95°F). Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

### Seveso Directive - Reporting thresholds (in tonnes)

#### Danger criteria

Category	Notification and MAPP threshold	Safety report threshold
P5c: Flammable liquids 2 and 3 not falling under P5a or P5b	5000	50000

### 7.3 Specific end use(s)

- Recommendations** : Not available.

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2015/830

Magnetic Chalkboard Paint

## SECTION 7: Handling and storage

**Industrial sector specific solutions** : Not available.

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

### 8.1 Control parameters

#### Occupational exposure limits

Product/ingredient name	Exposure limit values
Alkanes, C9-12-iso-	<b>EH40/2005 WELs (United Kingdom (UK), 10/2007).</b> STEL: 850 mg/m <sup>3</sup> , (as turpentine) 15 minutes. Form: Vapour TWA: 566 mg/m <sup>3</sup> , (as turpentine (100 ppm)) 8 hours. Form: Vapour

**Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### DNELs/DMELs

No DNELs/DMELs available.

#### PNECs

No PNECs available

### 8.2 Exposure controls

**Appropriate engineering controls** : Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn.

#### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields. Recommended: safety glasses with side-shields (EN 166)

#### Skin protection

#### Hand protection

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2015/830

Magnetic Chalkboard Paint

## SECTION 8: Exposure controls/personal protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

**Gloves** : For prolonged or repeated handling, use the following type of gloves:

Recommended: > 8 hours (breakthrough time): nitrile rubber (0.5mm)

The recommendation for the type or types of glove to use when handling this product is based on information from the following source:

EN 374-3 : 2003

The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

**Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. Refer to European Standard EN 1149 for further information on material and design requirements and test methods. Recommended: Wear overalls or long sleeved shirt. (EN 1149-1)

**Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: organic vapour filter (Type A) (EN 140)

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

<b>Physical state</b>	: Liquid.
<b>Colour</b>	: Black.
<b>Odour</b>	: Hydrocarbon.
<b>Odour threshold</b>	: Not available.
<b>pH</b>	: Not available.
<b>Melting point/freezing point</b>	: -20°C
<b>Initial boiling point and boiling range</b>	: >160°C
<b>Flash point</b>	: Closed cup: 40°C
<b>Evaporation rate</b>	: 0,2 (butyl acetate = 1)
<b>Flammability (solid, gas)</b>	: Flammable in the presence of the following materials or conditions: open flames, sparks and static discharge, heat and shocks and mechanical impacts. Vapour may travel a considerable distance to source of ignition and flash back.

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2015/830

Magnetic Chalkboard Paint

## SECTION 9: Physical and chemical properties

<b>Upper/lower flammability or explosive limits</b>	: Lower: 0,6% Upper: 7%
<b>Vapour pressure</b>	: 0,7 kPa [room temperature]
<b>Vapour density</b>	: >1 [Air = 1]
<b>Relative density</b>	: 1,51 to 1,52
<b>Solubility(ies)</b>	: Partially soluble in the following materials: acetone. Very slightly soluble in the following materials: methanol. Insoluble in the following materials: cold water, hot water, diethyl ether and n-octanol.
<b>Partition coefficient: n-octanol/ water</b>	: Not available.
<b>Auto-ignition temperature</b>	: 250°C
<b>Decomposition temperature</b>	: Not available.
<b>Viscosity</b>	: Dynamic (room temperature): 1000 to 1300 mPa·s Kinematic (40°C): >0,205 cm <sup>2</sup> /s
<b>Explosive properties</b>	: Non-explosive in the presence of the following materials or conditions: open flames, sparks and static discharge, heat and shocks and mechanical impacts.
<b>Oxidising properties</b>	: Not available.

### 9.2 Other information

No additional information.

## SECTION 10: Stability and reactivity

<b>10.1 Reactivity</b>	: No specific test data related to reactivity available for this product or its ingredients.
<b>10.2 Chemical stability</b>	: Stable under recommended storage and handling conditions (see Section 7).
<b>10.3 Possibility of hazardous reactions</b>	: Under normal conditions of storage and use, hazardous reactions will not occur.
<b>10.4 Conditions to avoid</b>	: When exposed to high temperatures may produce hazardous decomposition products.
<b>10.5 Incompatible materials</b>	: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.
<b>10.6 Hazardous decomposition products</b>	: Under normal conditions of storage and use, hazardous decomposition products should not be produced. If involved in a fire, toxic gases including CO, CO <sub>2</sub> and smoke can be generated.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity



Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2015/830

Magnetic Chalkboard Paint

**SECTION 11: Toxicological information**

Product/ingredient name	Result	Species	Dose	Exposure
Alkanes, C9-12-iso- 1-isopropyl-2, 2-dimethyltrimethylene diisobutyrate	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
	LC50 Inhalation Vapour	Rat	>5,3 mg/l	6 hours
	LD50 Dermal	Guinea pig	>18900 mg/kg	-
	LD50 Oral	Mouse	>6400 mg/kg	-
	LD50 Oral	Rat	>9600 mg/kg	-

**Conclusion/Summary** : Based on available data, the classification criteria are not met.**Acute toxicity estimates**

Not available.

**Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
Alkanes, C9-12-iso- 1-isopropyl-2, 2-dimethyltrimethylene diisobutyrate	Skin - Mild irritant	Rabbit	-	-	-
	Eyes - Mild irritant	Rabbit	-	-	-
	Skin - Oedema	Rabbit	0	-	-
	Eyes - Cornea opacity	Rabbit	0	-	-
	Skin - Mild irritant	Guinea pig	-	5 Grams	-
	Skin - Mild irritant	Human	-	504 hours 1 Percent Intermittent	-

**Conclusion/Summary****Skin** : Based on available data, the classification criteria are not met.**Eyes** : Based on available data, the classification criteria are not met.**Respiratory** : Based on available data, the classification criteria are not met.**Sensitisation**

Product/ingredient name	Route of exposure	Species	Result
Alkanes, C9-12-iso-	skin	Rabbit	Not sensitizing

**Conclusion/Summary****Skin** : Based on available data, the classification criteria are not met.**Respiratory** : Based on available data, the classification criteria are not met.**Mutagenicity****Conclusion/Summary** : Based on available data, the classification criteria are not met.**Carcinogenicity****Conclusion/Summary** : Based on available data, the classification criteria are not met.**Reproductive toxicity****Conclusion/Summary** : Based on available data, the classification criteria are not met.**Teratogenicity****Conclusion/Summary** : Based on available data, the classification criteria are not met.**Specific target organ toxicity (single exposure)**

Not available.

**Specific target organ toxicity (repeated exposure)**

Not available.

**Aspiration hazard**

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2015/830

Magnetic Chalkboard Paint

## SECTION 11: Toxicological information

Product/ingredient name	Result
Alkanes, C9-12-iso-	ASPIRATION HAZARD - Category 1

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Short term exposure

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

#### Long term exposure

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

#### Potential chronic health effects

Not available.

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

**General** : Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

**Carcinogenicity** : No known significant effects or critical hazards.

**Mutagenicity** : No known significant effects or critical hazards.

**Teratogenicity** : No known significant effects or critical hazards.

**Developmental effects** : No known significant effects or critical hazards.

**Fertility effects** : No known significant effects or critical hazards.

**Other information** : Not available.

## SECTION 12: Ecological information

### 12.1 Toxicity

There are no data available on the mixture itself.  
Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is classified for eco-toxicological properties accordingly. See Sections 2 and 3 for details.

Product/ingredient name	Result	Species	Exposure
Alkanes, C9-12-iso-	Acute EC50 >100 mg/l	Fish - Chaetogammarus marinus	24 hours
	Acute LC50 >1000 mg/l	Fish	96 hours
	Acute NOEC 1000 mg/l	Algae - pseudokirchneriella subcapitata	72 hours
	Chronic NOEC 0,025 mg/l	Daphnia spec.	21 days

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

### 12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
Alkanes, C9-12-iso- 1-isopropyl-2, 2-dimethyltrimethylene diisobutyrate	- OECD 301F	31,3 % - Inherent - 28 days >80 % - Readily - 28 days	- -	- -

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2015/830

Magnetic Chalkboard Paint

## SECTION 12: Ecological information

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Alkanes, C9-12-iso-1-isopropyl-2, 2-dimethyltrimethylene diisobutyrate	- -	- -	Not readily Readily

### 12.3 Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
Alkanes, C9-12-iso-1-isopropyl-2, 2-dimethyltrimethylene diisobutyrate	>3 4,1	- 5340	low high

### 12.4 Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

**Mobility** : Not available.

### 12.5 Results of PBT and vPvB assessment

**PBT** : Not applicable.

**vPvB** : Not applicable.

**12.6 Other adverse effects** : No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance.

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

**Hazardous waste** : Yes.

**Disposal considerations** : Do not allow to enter drains or watercourses. Dispose of according to all federal, state and local applicable regulations. If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

#### European waste catalogue (EWC)

The European Waste Catalogue classification of this product, when disposed of as waste, is:

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

#### Packaging

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.



Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2015/830

Magnetic Chalkboard Paint

## SECTION 13: Disposal considerations

- Disposal considerations** : Using information provided in this safety data sheet, advice should be obtained from the relevant waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.
- Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
<b>14.1 UN number</b>	Not regulated.	Not regulated.	UN1263	UN1263
<b>14.2 UN proper shipping name</b>	-	-	Paint.	Paint.
<b>14.3 Transport hazard class(es)</b>	-	-	3 	3 
<b>14.4 Packing group</b>	-	-	III	III
<b>14.5 Environmental hazards</b>	No.	No.	No.	No.
<b>Additional information</b>	Exempted according to 2.2.3.1.5 (Viscous substance exemption)  This class 3 material is not subject to regulation in packagings up to 450 L.		<b>Emergency schedules (EmS):</b> F-E + S-E  <b>Viscous substance exemption</b> This class 3 material can be considered non hazardous in packagings up to 30 L. Exempted according to 2.3.2.5 (Viscous substance exemption)	<b>Passenger and Cargo Aircraft</b> Quantity limitation: 60 L Packaging instructions: 355 <b>Cargo Aircraft Only</b> Quantity limitation: 220 L Packaging instructions: 366 <b>Limited Quantities - Passenger Aircraft</b> Quantity limitation: 10 L Packaging instructions: Y 344

- 14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2015/830

Magnetic Chalkboard Paint

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU Regulation (EC) No. 1907/2006 (REACH)

##### Annex XIV - List of substances subject to authorisation

###### Annex XIV

None of the components are listed.

###### Substances of very high concern

None of the components are listed.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

#### Other EU regulations

**VOC** : The provisions of Directive 2004/42/EC on VOC apply to this product. Refer to the product label and/or technical data sheet for further information.

**VOC for Ready-for-Use Mixture** : IIA/i. One-pack performance coatings. EU limit value for this product : 500g/l (2010.) This product contains a maximum of 375 g/l VOC.

**Europe inventory** : All components are listed or exempted.

#### Ozone depleting substances (1005/2009/EU)

Not listed.

#### Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

#### Seveso Directive

This product is controlled under the Seveso Directive.

##### Danger criteria

###### Category

P5c: Flammable liquids 2 and 3 not falling under P5a or P5b

#### National regulations

**Industrial use** : The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation. The provisions of the national health and safety at work regulations apply to the use of this product at work.

**References** : EH40/2005 Workplace exposure limits  
Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2015/830

#### International regulations

##### Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

##### Montreal Protocol (Annexes A, B, C, E)

Not listed.

##### Stockholm Convention on Persistent Organic Pollutants

Not listed.

##### Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

##### UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2015/830

Magnetic Chalkboard Paint

## SECTION 15: Regulatory information

**CN code** : 3208 20 90  
**UFI Code** : YY40-70QU-F000-SAVD

### International lists

#### National inventory

**Australia** : Not determined.  
**Canada** : Not determined.  
**China** : Not determined.  
**Japan** : **Japan inventory (ENCS)**: Not determined.  
**Japan inventory (ISHL)**: Not determined.  
**Malaysia** : Not determined.  
**New Zealand** : Not determined.  
**Philippines** : Not determined.  
**Republic of Korea** : Not determined.  
**Taiwan** : Not determined.  
**Turkey** : Not determined.  
**United States** : Not determined.

**15.2 Chemical safety assessment** : No Chemical Safety Assessment has been carried out.

## SECTION 16: Other information

Indicates information that has changed from previously issued version.

**Abbreviations and acronyms** : ATE = Acute Toxicity Estimate  
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
 DMEL = Derived Minimal Effect Level  
 DNEL = Derived No Effect Level  
 EUH statement = CLP-specific Hazard statement  
 PBT = Persistent, Bioaccumulative and Toxic  
 PNEC = Predicted No Effect Concentration  
 RRN = REACH Registration Number  
 vPvB = Very Persistent and Very Bioaccumulative

### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Flam. Liq. 3, H226	Expert judgment
Aquatic Chronic 4, H413	Expert judgment

### Full text of H-phrases referred to in sections 2 and 3

**Full text of abbreviated H statements** :

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

**Full text of classifications [CLP/GHS]** :

Aquatic Chronic 3, H412	LONG-TERM AQUATIC HAZARD - Category 3
Aquatic Chronic 4, H413	LONG-TERM AQUATIC HAZARD - Category 4
Asp. Tox. 1, H304	ASPIRATION HAZARD - Category 1
EUH066	Repeated exposure may cause skin dryness or cracking.
Flam. Liq. 3, H226	FLAMMABLE LIQUIDS - Category 3

**Date of printing** : 16/01/2018

**Date of issue/ Date of revision** : 16/01/2018

**Date of previous issue** : 16/01/2018

**Version** : 2

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 2015/830

*Magnetic Chalkboard Paint***SECTION 16: Other information****Notice to reader**

The information in this Safety Data Sheet is based on the present state of knowledge and current legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with. The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks, as required by other health and safety legislation.