

Timestep / 5

- Hardwearing, homogeneous sheet
- *Marbleized Grey and Tan, and Solid Grey, Black, and Tan. Specialized colors available call for more info*

SPECIFICATION



2.0mm
.08 in



N/A



N/A



Timestep
2m x 20m
6.56ft x 65ft

Timestep 5
1.5m x 20m
5ft x 65ft



3.2 kg/m²
5.88 lbs/yd²



GENERAL PERFORMANCE

EN 649
ASTM F1913
ASTM F1700
Agrément – 2.0; G5ws

2.0mm



REACTION TO FIRE

EN 13501-1 Class Bfl-S1
ASTM E662 <450
ASTM E648 Class 1*

{ EN ISO 9239-1 ≥8kw/m² (all gauges)
EN ISO 11925-2 Pass (all gauges)



SLIP RESISTANCE
EN 13893 Class DS
AS/NZS 4586 R9



ABRASION RESISTANCE
EN 649 Group M



MARITIME USAGE

Marine Equipment Directive †
96/98/EC as amended 2002/75/EC
SOLAS 74

† Timestep Only



HYGIENE

This product has been independently tested and results demonstrate that it inhibits the growth of MRSA. An effective cleaning regime is however, the most important defence against infection.



ELECTRICAL BEHAVIOUR (body voltage)

EN 1815 This product does not accumulate static charges above 2kV and is classified as 'antistatic'.



ENVIRONMENT

BRE Green Guide to Specifications A rating



APPLICATIONS

Timestep / 5 when used with a sprung sub floor is an ideal multipurpose dance surface, suitable for all forms of dance, Timestep can also be used as multipurpose sports, athletic surface



For information regarding handling and installation, adhesives, maintenance, applications and chemical resistance,
Call 800-523-0960



Stagestep Inc. 4701 Bath St #46, Philadelphia Pa 19137
215-636-9000 800-523-0960
www.stagestep.com

TIMESTEP / 5

HOMOGENOUS

PERFORMANCE AND PROPERTIES